

FIELD EQUIPMENT



The Beamex range of portable calibrators and communicators, temperature blocks and pressure generators



beamex
WORLD-CLASS CALIBRATION SOLUTIONS

Field equipment

Beamex is a technology and service company that develops, manufactures and markets high-quality calibration equipment, software, systems and services for the calibration and maintenance of process instruments. The company is a leading worldwide provider of integrated calibration solutions that meet even the most demanding requirements.



6

Success stories

10,000 companies worldwide use Beamex calibration solutions. Now you can read some of these success stories.



8

Solutions

Beamex solutions for paperless calibration, calibration in hazardous areas, plant commissioning as well as configuration and calibration of smart instruments.



19

MC6

HART
COMMUNICATION PROTOCOL

PROFIBUS

PROFIBUS



The Beamex MC6 is an advanced, high-accuracy field calibrator and communicator. It offers calibration capabilities for various signals. It also contains a full fieldbus communicator.



39

MC4



The Beamex MC4 is a compact-sized easy-to-use documenting process calibrator for pressure, electrical and temperature signals.



51

MC2

The Beamex MC2 series includes three different hand-held calibrators for field use: a pressure/electrical calibrator, a temperature/electrical calibrator and a multifunction calibrator.

63



MC5-IS



The Beamex MC5-IS is an ATEX and IECEx certified documenting calibrator designed for use in potentially explosive environments.

73



MC2-IS



The Beamex MC2-IS is an ATEX and IECEx certified calibrator designed for use in potentially explosive environments.

85



RTS24 temperature simulator

The Beamex RTS24 is a high precision instrument for the simulation of Pt-100 resistance thermometers.

87



MB metrology temperature block

The Beamex MB metrology temperature block is a portable temperature dry block delivering bath-level accuracy for industrial applications.

3

93



FB field temperature block

The Beamex FB field temperature block is an ideal temperature block for industrial field use. It is lightweight and easy to carry. It is a very fast dry block, yet it provides excellent accuracy.

101



POC6

The Beamex POC6 is an accurate and user-friendly automatic pressure output controller, providing regulated output from vacuum to 100 bar (1450 psi).

105



PG pressure generation

The PG series includes five different hand-held calibration pumps for pressure generation: PGXH, PGPH, PGM, PGL and PGV.

113



EXT external pressure modules

The Beamex EXT external pressure modules introduce new configuration possibilities and add flexibility, as it is possible to calibrate even more pressure ranges with the same calibrator.

FIELD EQUIPMENT FEATURE COMPARISON TABLE



FEATURE*	MC6	MC4
Electrical calibrator	●	●
Temperature calibrator	●	●
Number of internal pressure modules	3+Barometric	1+Barometric
Compatible with external pressure modules	●	●
ATEX / IECEx certified		
Documenting to PC (CMX software)	●	●
Datalogging	●	
HART communication	●	
FOUNDATION Fieldbus H1 communication	●	
Profibus PA communication	●	
Configuration of HART, Foundation Fieldbus H1 and Profibus PA instruments	●	
Pressure/temperature controller communication	●	
IP65 Water and dust proof	●	
Warranty period (excl. battery)	3 years	2 years

* Some of the features are optional.

MB MODEL RANGE

MB140 / MB140R -45 °C ... +140 °C
 MB155 / MB155R -30 °C ... +155 °C
 MB425 / MB425R +35 °C ... +425 °C
 MB700 / MB700R +50 °C ... +700 °C



FB MODEL RANGE

FB150 / FB150R -25 °C ... +150 °C
 FB350 / FB350R +33 °C ... +350 °C
 FB660 / FB660R +50 °C ... +660 °C





MC2-TE

MC2-MF

MC5-IS

MC2-IS

•

•

•

•

•

•

•

•

1+Barometric

3

Barometric

•

•

•

•

•

•

•

•

•

•

•

•

•

•

2 years

2 years

3 years

2 years

POC6

± 1 bar (±14.5 psi)

-1 to 6 bar (-14.5 to 87 psi)

-1 to 20 bar (-14.5 to 290 psi)

-1 to 70 bar (-14.5 to 1,015 psi)

-1 to 100 bar (-14.5 to 1,450 psi)

Special range within -1 to 100 bar (-14.5 to 1,450 psi)



SUCCESS STORIES



6

PHARMACEUTICAL AND HEALTHCARE AstraZeneca, Sweden

AstraZeneca is one of the world's leading biopharmaceutical companies with 30 manufacturing sites in 20 countries. In 2004, Beamex made a corporate agreement with AstraZeneca Sweden Operations. AstraZeneca decided to implement a completely new calibration system including Beamex's CMX calibration management software licenses, training and software support. After implementing the new calibration management process, the entire process takes place digitally, from measurement to signing and archiving. The company performs about 22,000 calibrations annually, which previously engaged 50 employees. Today, the same work can be accomplished with only 15 people.

Solution

- Beamex CMX calibration software
- Beamex MC5 multifunction calibrators

Main benefits

- 1 year pay-off
- Number of databases reduced from 12 to 1
- All paperwork replaced by an electronic calibration process
- Less frequent calibration intervals
- Less labor intense
- Improved overall quality of the calibration process

SERVICE AND AUTOMATION Endress+Hauser, Germany

Endress+Hauser is the leading international supplier of measuring instruments, services and solutions for process automation. In the past E+H on-site service teams used single signal calibration tools; those tools had long recalibration turn-around-time and caused high internal management effort. Now, however, there is just one multifunction calibration device, one supplier and one certificate replacing 3 to 5 previous devices, certificates and supplier. Since 2006, Endress+Hauser has relied on Beamex process calibrators as well as the services provided by GERMEX GmbH, the exclusive distributor and Premium Partner of Beamex products in Germany. Endress+Hauser has chosen Beamex MC-calibrators as global standard tools to be used for improved efficiency in on-site calibration services and start-up commissioning.

Solution

- Beamex MC6 advanced field calibrator and communicator
- Beamex MC5 multifunction calibrators with Foundation Fieldbus communication
- Beamex MC2 calibrators
- Beamex CMX calibration management software

Main benefits

- Streamlined calibration process
- Short investment payback time
- Decrease in downtime
- Less maintenance costs, due to reduction of calibration tools
- Equipment easy to use
- Reliability, quality and efficiency of services



FOOD AND BEVERAGE Heineken España, Spain

The new Heineken España S.A. (JUMBO) brewery in Sevilla is the most modern and productive plant in Europe, allowing the company to remain Spain's market leader in beer. The new plant needed a tool to make calibration work easier, store all calibration results, indicate the calibration history trend and provide quick access to calibration data. These factors led Heineken to choose the Beamex CMX calibration software with the Beamex MC5 multifunction calibrator.

Each instrument that is calibrated regularly has its calibration procedure including the initial calibration date, due date and all calibration related information. Calibration work orders are automatically generated and entered into the SAP PM management system. Once the calibrations are completed, the data is stored in the CMX.

Solution

- Beamex CMX calibration software (with Pocket PC option)
- Beamex MC5 multifunction calibrator

Main benefits

- Streamlined and automated calibration procedures (e.g. documentation, calibration work procedures)
- Efficient, practical and accurate working methods, minimizing the possibilities for human errors
- Safe calibration system that adheres to regulations (ISO 9001, ISO 14001)
- Improved quality, cost savings and fast ROI for the new calibration system

WATER AND WASTE WATER SERVICE Miami-Dade WASH, USA

One of the largest public utilities in the United States, the Miami-Dade Water and Sewer Department (WASH), a department of Miami-Dade county, provides direct service to more than 420,000 customers and employs more than 2,500 workers.

Miami-Dade WASH utilizes the documenting Beamex MC5 multifunction calibrators and Beamex CMX Professional calibration management software, part of the Beamex integrated calibration solution. The MC5 calibrators calibrate the most important plant instruments. CMX is integrated into Miami-Dade WASH's maintenance management software, Infor EAM Enterprise edition, to schedule, perform maintenance and document results.

Solution

- Beamex MC5 multifunction calibrators
- Beamex CMX Professional calibration management software

Main benefits

- Major improvements in efficiency
- Traceability and accountability
- Safety
- Enhanced quality
- Robust and reliable software
- Integrated system

SOLUTIONS

PAPERLESS CALIBRATION

A paperless calibration system comprising documenting calibrators and calibration software improves quality and cuts costs. The business benefits are significant for companies that use software-based calibration systems. The entire calibration process – from initial recording of calibration data to historical trend analysis – will take less time, whilst virtually eliminating mistakes and manual errors.

8



RELATED PRODUCTS

Beamex MC6 calibrator

Beamex MC5-IS calibrator

Beamex MC4 calibrator

CMX Light calibration software

CMX Professional calibration software

CMX Enterprise calibration software

Beamex Business Bridge



Traditional paper-based systems

While using a manual, paper-based system requires little or no investment in new technology or IT systems, it is extremely labor-intensive and means that historical trend analysis of calibration results becomes very difficult. In addition, accessing calibration data quickly is not easy. Paper systems are time consuming, they soak up lots of company resources and manual (typing) errors are commonplace. Dual effort and the re-keying of calibration data into multiple databases become significant costs to the business.

Business benefits of paperless calibration

The business benefits of a paperless calibration system are significant. The entire calibration process – from initial recording of calibration data to historical trend analysis – will take less time, virtually eliminating mistakes and manual errors. In turn, this means that operators, engineers and management will have more confidence in the data, particularly when it comes to plant audits. In addition, this greater confidence in calibration data leads to a better understanding and analysis of business performance and KPIs (particularly if the calibration software is integrated into other business IT systems such as a CMMS) leading to improved processes, increased efficiency and reduced plant downtime.

STEP-BY-STEP

BEAMEX ICS INTEGRATED CALIBRATION SOLUTION

THE CALIBRATION PROCESS

10




The Beamex CMX alerts what needs to be calibrated and when

- Easy, fast and efficient
- No need to search archived paper files



Download calibration procedures and instructions from the software to the MC6

- Fast procedure
- No pen, paper or notepads needed



Create, store and manage calibration information safely and efficiently with the software

- All calibration data is stored and managed in the CMX database
- Calibration certificates, reports and labels in electronic format, on paper or both
- All documentation in the CMX is auditable and traceable (e.g. ISO 17025, cGMP, 21 CFR Part 11)



Integration to a maintenance management system

- Plant hierarchy and work orders are stored in ERP/CMMS (e.g. SAP, Maximo) and from there transferred to the CMX, which stores all calibration procedures, standards and results
- When calibration work has been performed, the CMX sends acknowledgement of the calibration back to ERP/CMMS



3.

Perform instrument calibration and data collection with the MC6

- The MC6 replaces many individual measurement devices and calibrators
- Automated calibration is fast



4.

Upload calibration results to the software

- Automatically download calibration results back to the software
- Data transfer is fast and efficient, writing mistakes are eliminated



78977348759834759843
 67984854546546
 798746546546513213213
 62587965836458734657
 665387875684653400

SOLUTIONS CALIBRATION IN HAZARDOUS AREAS

12

There are industrial environments where calibrations should not only be made accurately and efficiently, but also safely. When safety becomes a top priority in calibration, intrinsically safe calibrators are required. Intrinsic safety (IS) is a protection technique for the safe operation of electronic equipment in explosive environments. The idea behind intrinsic safety is to be assured that the available electrical and thermal energy in the system is always low enough that ignition of the hazardous atmosphere cannot occur.



RELATED PRODUCTS

Beamex MC5-IS calibrator

Beamex MC2-IS calibrator





Intrinsically safe calibrators

An intrinsically safe calibrator is designed to be incapable of causing ignition in the surrounding environment with flammable materials, such as gases, mists, vapors or combustible dust. Intrinsically safe calibrators are also often referred to being “Ex calibrators” or “calibrators for Ex Areas”.

Where is intrinsically safe calibration required

Many industries require intrinsically safe calibration equipment. Intrinsically safe calibrators are designed for potentially explosive environments, such as oil refineries, rigs and processing plants, gas pipelines and distribution centres, petrochemical and chemical plants, as well as pharmaceutical plants. Basically, any potentially explosive industrial environment can benefit from using intrinsically safe calibrators.

Benefits of using intrinsically safe calibrators

Safest possible technique. Intrinsically safe calibrators are safe for employees, as they can be safely used in environments where the risk of an explosion exists. In addition, intrinsically safe calibrators are the only technique permitted for Zone 0 environments (explosive gas and air mixture is continuously present or present for a long time).

Performance and functionality. Multifunctional intrinsically safe calibrators provide the functionality and performance of regular industrial calibration devices, but in a safe way. They can be used for the calibration of pressure, temperature and electrical signals. A documenting intrinsically safe calibrator, such as the Beamex MC5-IS, provides additional efficiency improvements with its seamless communication with calibration software. This eliminates the need of manual recording of calibration data and improves the quality and productivity of the entire calibration process.

SOLUTIONS

CALIBRATION AND CONFIGURATION OF SMART INSTRUMENTS

14

Fieldbus is becoming more and more common in today's instrumentation and fieldbus transmitters must also be calibrated. The fieldbus functionality includes reading the digital output of the fieldbus transmitter, changing the configurations of transmitters and trimming of transmitters.



RELATED PRODUCTS

Beamex MC6 calibrator

Beamex MC5-IS calibrator





Fieldbus transmitters must also be calibrated

Are you aware that fieldbus transmitters need to be calibrated just like any other transmitters? The main difference between fieldbus and conventional transmitters is that the output signal is a fully digital fieldbus signal. Although modern fieldbus transmitters have been improved compared to older transmitter models, it does not eliminate the need for calibration. Major time-savings can also be achieved by using the MC6 HART and/or Fieldbus functionality to enter transmitter data into the MC6 memory where the data can then be populated to the CMX calibration software instead of manually entering the data into the calibration database.

There are no such instruments, neither digital nor analog, that would remain stable indefinitely. Therefore, the “digitality” of an instrument does not mean that calibration is unnecessary. There are also many other reasons, such as quality systems and regulations, that make the periodic calibrations compulsory.

Beamex's fieldbus calibration solution

Beamex offers two products for calibrating fieldbus transmitters: MC5-IS (intrinsically safe) and MC6.

The MC6 is a one-of-a-kind measurement device being an advanced field calibrator and full multi-bus communicator. The MC5-IS and MC6 can be used to calibrate HART, FOUNDATION Fieldbus H1 and Profibus PA instruments.



SOLUTIONS

COMMISSIONING

Successful commissioning of process instrumentation is an essential requirement for ideal plant performance. A plant, or any defined part of a plant, is ready for commissioning when the plant has achieved mechanical completion. Plant commissioning involves activities such as checking to ensure plant construction is complete and complies with the documented design or approved (authorized and recorded) design changes. In general, commissioning activities are those associated with preparing or operating the plant or any part of the plant prior to the initial start-up and are frequently undertaken by the owner or joint owner/contractor team.

16



RELATED PRODUCTS

Beamex MC6 calibrator

Beamex MC4 calibrator

Beamex CMX Professional calibration software

Beamex CMX Enterprise calibration software



Calibration and commissioning of instrumentation

New process instrumentation is typically configured and calibrated by the manufacturer prior to installation. However, instruments are often recalibrated upon arrival at the site, especially if there has been obvious damage in transit or storage. There are also many other reasons why instruments should be calibrated during the commissioning phase before start-up.

Assuring transmitter quality

First of all, the fact that an instrument or transmitter is new does not automatically mean that it is within required specifications. Calibrating a new instrument before installing or using it is a quality assurance task. You can check the overall quality of the instrument to see if it is defective and to ensure it has the correct, specified settings.

Reconfiguring a transmitter

The new uninstalled instrument or transmitter may have the correct, specified settings. However, it is possible that the original planned settings are not valid anymore and they need to be changed. By calibrating an instrument you can check the settings of the instrument. After you have performed this task, it is possible to reconfigure the transmitter, when the initial planned


specifications have been changed. Calibration is therefore a key element in the process of reconfiguring an uninstalled transmitter.

Monitoring the quality and stability of a transmitter

When calibration procedures are performed for an uninstalled instrument, the calibration serves also future purposes. By calibrating the transmitter before installation and on a regular basis thereafter, it is possible to monitor the stability of the transmitter.

Entering the necessary transmitter data into a calibration database

By calibrating an instrument before installation it is possible to enter all the necessary instrument data into the calibration database, as well as to monitor the instrument's stability, as was explained in the previous paragraph. The transmitter information is critical in defining the quality of the instrument and for planning the optimal calibration interval of the instrument.



Beamex MC6

ADVANCED FIELD CALIBRATOR AND COMMUNICATOR



19

The impossible made possible:
combining advanced functionality with ease-of-use





The impossible made possible: combining advanced functionality with ease-of-use

Beamex MC6 is an advanced, high-accuracy field calibrator and communicator. It offers calibration capabilities for pressure, temperature and various electrical signals. The MC6 also contains a full fieldbus communicator for HART, FOUNDATION Fieldbus and Profibus PA instruments.

The usability and ease-of-use are among the main features of the MC6. It has a large 5.7" color touch-screen with a multilingual user interface. The robust IP65-rated dust- and water-proof casing, ergonomic design and light weight make it an ideal measurement device for field use in various industries, such as the pharmaceutical, energy, oil and gas, food and beverage, service as well as the petrochemical and chemical industries.

The MC6 is one device with five different operational modes, which means that it is fast and easy to use, and you can carry less equipment in the field. The operation modes are: meter, calibrator, documenting calibrator, data logger and fieldbus communicator. In addition, the MC6 communicates with Beamex CMX calibration software, enabling fully automated and paperless calibration and documentation.

In conclusion, the MC6 is more than a calibrator.



MC6 main features

Accuracy

High-accuracy, advanced field calibrator and communicator.

Usability

Combines advanced functionality with ease-of-use.

Versatility

Versatile functionality beyond traditional calibration applications.

Communicator

Full multi-bus communicator for HART, FOUNDATION Fieldbus and Profibus PA instruments.

Integration

Automates calibration procedures for paperless calibration management.





High-accuracy, advanced field calibrator and communicator

Accredited calibration certificate as standard

Each MC6 is delivered with a traceable, accredited calibration certificate as standard. The certificate includes calibration and uncertainty data from the calibration laboratory. The calibration laboratory's Scope of Accreditation can be found on Beamex's website (www.beamex.com).

Summary of accuracy figures

The MC6 has specifications for short-term accuracy and for 1-year total uncertainty. Brief summary of the accuracy figures:

- Pressure accuracy starting from $\pm(0.005\% \text{ FS} + 0.0125\% \text{ of reading})$.
- Temperature – RTD temperature measurement accuracy starting from $\pm 0.011 \text{ }^\circ\text{C}$.
- Electric – current measurement accuracy starting from $\pm(0.75 \mu\text{A} + 0.0075\% \text{ of reading})$.

23

Designed for field use

User-friendly interface

The MC6 has a large 5.7" color touch-screen with high resolution and an effective adjustable backlight. In addition, the MC6 has a membrane keypad. A soft number keypad and alphabetical QWERTY text keypad will appear whenever necessary for easy number/text entries.

Robust, lightweight and ergonomic design

The MC6 has rechargeable lithium-ion polymer batteries, which are durable and charge up quickly. The user interface keeps you up to date on the remaining operation time in hours and minutes, making it easy to follow how long the battery will last. Once the unit is switched on, it is ready to use in just a few seconds. The case is ergonomic and water-/dust-proof (IP65). There are two types of cases available: a slim case when internal pressure modules are not needed and an extended version, which provides room for the internal pressure modules.



USER-INTERFACE MODES

1. Meter

The meter mode is designed for simple and easy measurement of signals. Oftentimes, you may need to measure something quickly and easily. Often a simple multi-meter is used for this purpose, as it is easy to use. Some multifunctional calibrators may be too slow and difficult to use, so it is easier to just choose the simpler meter. The meter mode in MC6 is optimized for this type of simple and easy metering.




2. Calibrator

The calibrator mode is designed for calibrating various process instruments. Oftentimes, you need to check and calibrate a certain process instrument/transmitter. Transmitters typically have an input and an output. So you either need to have two devices, or a device capable of doing two things simultaneously. The calibrator mode in MC6 is optimized for this type of use.



3. Data logger

The data logger is designed for logging various measurement results. Often in industry, there is a need to measure signals for shorter or longer periods and to save the results in a memory for later analysis. This may be related to troubleshooting, surveillance or calibration. The data logger mode in MC6 is optimized for this type of use.






4. Documenting calibrator

The documenting calibrator mode is designed for the process instrument calibration and documenting of the calibration results. In today's process plant, calibrations often have to be documented. Without a documenting calibrator, documentation must be done manually, which takes a lot of precious time and is prone to error. The documenting calibrator mode in MC6 is optimized for use as a documenting process calibrator.



5. Communicator

The communicator mode is designed to communicate with Fieldbus instruments. In today's process plants, smart instrumentation is being used to an increasing degree. Therefore, engineers need to use communicators or configuration software. Most of this instrumentation is HART, FOUNDATION Fieldbus or Profibus PA. The communicator mode in MC6 is optimized for communicator use.



6. Settings

The settings mode allows you to edit the calibrator's various settings.



78977340759834755843
 87984654546546
 796746546546513213213
 62587965836458734657
 65387875684653400



Full multi-bus field communicator for HART, FOUNDATION Fieldbus and Profibus PA instruments

Communicator

The communicator mode is a full multi-bus communicator for HART, FOUNDATION Fieldbus and Profibus PA instruments. All of the communicator electronics for all protocols are built into the MC6, including internal loop power supply with various required impedances for different buses, which means there is no need to use any external loop supply or resistors.

Multi-bus communicator

The MC6 communicator can be used with all types of fieldbus instruments, not only pressure and temperature transmitters. All 3 protocols can be simultaneously installed into an MC6, and therefore the very same device can be used as a HART, FOUNDATION Fieldbus and Profibus PA communicator. With the MC6, you can access all parameters in all blocks of a fieldbus instrument. Its memory stores device descriptions for the fieldbus instruments. When new instruments are introduced on the market, new device description files will be made available and can be easily downloaded into the memory.



Additional features

FEATURE	SPECIFICATION
Scaling	A versatile programmable scaling function allows user to scale any measurement or generation unit into any other unit. Supports also rooting transfer function for flow applications. Also, custom units and custom transfer functions are supported.
Alarm	An alarm that can be programmed with high or low limit, as well as slow rate or fast rate limit.
Leak test	A dedicated function that can be used to analyse a change in any measurement. Can be used for pressure leak testing as well as any stability testing.
Damping	A programmable damping allows user to filter any measurement.
Resolution	Possibility to change the resolution of any measurement by reducing or adding decimals.
Step	A programmable step function for any generation or simulation.
Ramp	A programmable ramp function for any generation or simulation.
Quick access	Possibility to set four (4) quick access buttons in generation to easily generate the programmed values.
Spinner	Possibility to easily step any digit in the generation value up or down.
Additional info	Allow user to see additional information in the screen such as: min, max, rate, average, internal temperature, RTD sensor's resistance, thermocouple's thermovoltage, range min/max, etc.
Function info	Displays more information on the selected function.
Connection diagrams	Displays a picture showing where to connect the test leads with the selected function.
Calibration references	Allows you to document the additional references that were used during the calibration and passes on the information to Beamex CMX calibration software.
Users	Possibility to create a list of persons in the documenting calibrator in order to easily select who did the calibration.
Custom pressure unit	Large number of custom pressure units can be created.
Custom RTD sensor	Unlimited number of custom RTD sensors can be created using the Callendar van Dusen coefficients.
Custom point sets	Unlimited number of custom point sets can be created in calibration of an instrument, or step generation.
Custom transfer function	Unlimited number of custom transfer functions can be created in calibration of an instrument or in scaling function.

Note: All functions are not available in all user interface modes.



Specifications

GENERAL SPECIFICATIONS

FEATURE	VALUE
Display	5.7" Diagonal 640 x 480 TFT LCD module
Touch panel	5-wire resistive touch screen
Keyboard	Membrane keyboard
Backlight	LED backlight, adjustable brightness
Weight	Extended case: 1.5...2.0 kg (3.3...4.4 lb) Flat case: 1.5 kg (3.3 lb)
Dimensions	Extended case: 200 mm × 230 mm × 70 mm (D × W × H) (7.87 in × 9.06 in × 2.76 in) Flat case: 200 mm × 230 mm × 57 mm (D × W × H) (7.87 in × 9.06 in × 2.24 in)
Battery type	Rechargeable lithium-ion polymer, 4200 mAh, 11.1V
Charging time	Approximately 4 hours
Charger supply	100...240 VAC, 50–60 Hz
Battery operation	10...16 hours
Operating temperature	–10...45 °C (14...113 °F)
Operating temperature while charging batteries	0...30 °C (32...86 °F)
Storage temperature	–20...60 °C (–4...113 °F)
Specifications valid	–10...45 °C, unless other mentioned
Humidity	0...80% R.H. non condensing
Warmup time	Specifications valid after a 5 minute warmup period.
Max. input voltage	30 V AC, 60 V DC
Display update rate	3 readings/second
Safety	Directive 2006/95/EC, EN 61010-1:2001
EMC	Directive 2004/108/EC, EN 61326-1:2006
Ingress protection	IP65
Drop	IEC 60068-2-32. 1 meter (3.28 ft)
Vibration	IEC 60068-2-64. Random, 2 g, 5...500 Hz
Max altitude	3,000 m (9,842 ft)
Warranty	Warranty 3 Years. 1 year for battery pack. Warranty extension programs are also available.

MEASUREMENT, GENERATION AND SIMULATION FUNCTIONS

- Pressure measurement (internal/external pressure modules)
 - Voltage measurement (± 1 V and $-1...60$ VDC)
 - Current measurement (± 100 mA) (internal or external supply)
 - Frequency measurement (0...50 kHz)
 - Pulse counting (0...10 Mpulse)
 - Switch state sensing (dry/wet switch)
 - Built-in 24 VDC loop supply (low impedance, HART impedance or FF/PA impedance)
 - Voltage generation (± 1 V and $-3...24$ VDC)
 - Current generation (0...55 mA) (active/passive, i.e. Internal or external supply)
 - Resistance measurement, two simultaneous channels (0...4 k Ω)
 - Resistance simulation (0...4 k Ω)
 - RTD measurement, two simultaneous channels
 - RTD simulation
 - TC measurement, two simultaneous channels (universal connector/mini-plug)
 - TC simulation
 - Frequency generation (0...50 kHz)
 - Pulse queue generation (0...10 Mpulse)
 - HART communicator
 - FOUNDATION Fieldbus communicator
 - Profibus PA communicator
- (Some of the above functions are optional)

PRESSURE MEASUREMENT

INTERNAL MODULES	EXTERNAL MODULES	UNIT	RANGE ⁽³⁾	RESOLUTION	ACCURACY ⁽¹⁾ (±)	1 YEAR UNCERTAINTY (±) ⁽²⁾
PB	EXT B	kPa a mbar a psi a	70 to 120 700 to 1200 10.15 to 17.4	0.01 0.1 0.001	0.3 mbar	0.05 kPa 0.5 mbar 0.0073 psi
P10mD	EXT10mD	kPa diff mbar diff iwc diff	±1 ±10 ±4	0.0001 0.001 0.001	0.05% Span	0.05% Span + 0.1% RDG
P100m	EXT100m	kPa mbar iwc	0 to 10 0 to 100 0 to 40	0.0001 0.001 0.001	0.015% FS + 0.0125% RDG	0.025% FS + 0.025% RDG
P400mC	EXT400mC	kPa mbar iwc	±40 ±400 ±160	0.001 0.01 0.001	0.01% FS + 0.0125% RDG	0.02% FS + 0.025% RDG
P1C	EXT1C	kPa bar psi	±100 ±1 -14.5 to 15	0.001 0.00001 0.0001	0.007% FS + 0.0125% RDG	0.015% FS + 0.025% RDG
P2C	EXT2C	kPa bar psi	-100 to 200 -1 to 2 -14.5 to 30	0.001 0.00001 0.0001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
P6C	EXT6C	kPa bar psi	-100 to 600 -1 to 6 -14.5 to 90	0.01 0.0001 0.001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
P20C	EXT20C	kPa bar psi	-100 to 2000 -1 to 20 -14.5 to 300	0.01 0.0001 0.001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
P60	EXT60	kPa bar psi	0 to 6000 0 to 60 0 to 900	0.1 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
P100	EXT100	MPa bar psi	0 to 10 0 to 100 0 to 1500	0.0001 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
P160	EXT160	MPa bar psi	0 to 16 0 to 160 0 to 2400	0.0001 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
-	EXT250	MPa bar psi	0 to 25 0 to 250 0 to 3700	0.001 0.01 0.1	0.007% FS + 0.0125% RDG	0.015% FS + 0.025% RDG
-	EXT600	MPa bar psi	0 to 60 0 to 600 0 to 9000	0.001 0.01 0.1	0.007% FS + 0.01% RDG	0.015% FS + 0.025% RDG
-	EXT1000	MPa bar psi	0 to 100 0 to 1000 0 to 15000	0.001 0.01 0.1	0.007% FS + 0.01% RDG	0.015% FS + 0.025% RDG

¹⁾ Accuracy includes hysteresis, nonlinearity and repeatability (k=2).

²⁾ Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long term stability for mentioned period (k=2).

³⁾ Every internal/external gauge pressure module's range may be displayed also in absolute pressure if the barometric module (PB or EXT B) is installed/connected.

Maximum number of internal pressure modules is 3 gauge/differential pressure modules and one barometric (PB) module in the extended case. The flat case has room for internal barometric module only. Both cases have connection for external pressure modules.

External pressure modules are also compatible with Beamex MC2, MC4 and MC5 family calibrators.

SUPPORTED PRESSURE UNITS

Pa, kPa, hPa, MPa, mbar, bar, gf/cm², kgf/cm², kgf/m², kp/cm², lbf/ft², psi, at, torr, atm, ozf/in², iwc, inH₂O, ftH₂O, mmH₂O, cmH₂O, mH₂O, mmHg, cmHg, mHg, inHg, mmHg(0 °C), inHg(0 °C), mmH₂O(60°F), mmH₂O(68°F), mmH₂O(4 °C), cmH₂O(60°F), cmH₂O(68°F), cmH₂O(4 °C), inH₂O(60°F), inH₂O(68°F), inH₂O(4 °C), ftH₂O(60°F), ftH₂O(68°F), ftH₂O(4 °C).
Large number of user pressure units can be created.

TEMPERATURE COEFFICIENT

<±0.001% RDG/ °C outside 15–35 °C (59–95 °F).

P10mD / EXT10mD: < ±0.002% Span/ °C outside 15–35 °C (59–95 °F)

MAX OVERPRESSURE

2 times the nominal pressure. Except following modules;

PB/EXTB: 1200 mbar abs (35.4 inHg abs). P10mD/EXT10mD: 200 mbar (80 iwc). EXT600: 900 bar (13000 psi). EXT1000: 1000 bar (15000 Psi).

PRESSURE MEDIA

Modules up to P6C/EXT6C: dry clean air or other clean, inert, non-toxic, non-corrosive gases. Modules P20C/EXT20C and higher: clean, inert, non-toxic, non-corrosive gases or liquids.

WETTED PARTS

AISI316 stainless steel, Hastelloy, Nitrile rubber

PRESSURE CONNECTION

PB/EXTB: M5 (10/32") female.

P10mD/EXT10mD: Two M5 (10/32") female threads with hose nipples included.

P100m/EXT100m to P20C/EXT20C: G1/8" (ISO228/1) female. A conical 1/8"

BSP male with 60° internal cone adapter included for Beamex hose set.

P60, P100, P160: G1/8" (ISO228/1) female.

EXT60 to EXT1000: G 1/4" (ISO228/1) male.

TC MEASUREMENT & SIMULATION

TC1 measurement & simulation / TC2 measurement

TYPE	RANGE (°C)	RANGE (°C)	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY (±) ⁽²⁾
B ⁽³⁾	0...1820	0...200	⁽⁸⁾	⁽⁴⁾
		200...500	1.5 °C	2.0 °C
		500...800	0.6 °C	0.8 °C
		800...1820	0.4 °C	0.5 °C
R ⁽³⁾	-50...1768	-50...0	0.8 °C	1.0 °C
		0...150	0.6 °C	0.7 °C
		150...400	0.35 °C	0.45 °C
		400...1768	0.3 °C	0.4 °C
S ⁽³⁾	-50...1768	-50...0	0.7 °C	0.9 °C
		0...100	0.6 °C	0.7 °C
		100...300	0.4 °C	0.55 °C
		300...1768	0.35 °C	0.45 °C
E ⁽³⁾	-270...1000	-270...-200	⁽⁸⁾	⁽⁴⁾
		-200...0	0.05 °C + 0.04% RDG	0.07 °C + 0.06% RDG
		0...1000	0.05 °C + 0.003% RDG	0.07 °C + 0.005% RDG
J ⁽³⁾	-210...1200	-210...-200	⁽⁸⁾	⁽⁴⁾
		-200...0	0.06 °C + 0.05% RDG	0.08 °C + 0.06% RDG
		0...1200	0.06 °C + 0.003% RDG	0.08 °C + 0.006% RDG
K ⁽³⁾	-270...1372	-270...-200	⁽⁸⁾	⁽⁴⁾
		-200...0	0.08 °C + 0.07% RDG	0.1 °C + 0.1% RDG
		0...1000	0.08 °C + 0.004% RDG	0.1 °C + 0.007% RDG
		1000...1372	0.012% RDG	0.017% RDG
N ⁽³⁾	-270...1300	-270...-200	⁽⁸⁾	⁽⁴⁾
		-200...-100	0.15% RDG	0.2% RDG
		-100...0	0.11 °C + 0.04% RDG	0.15 °C + 0.05% RDG
		0...800	0.11 °C	0.15 °C
		800...1300	0.06 °C + 0.006% RDG	0.07 °C + 0.01% RDG
T ⁽³⁾	-270...400	-270...-200	⁽⁸⁾	⁽⁴⁾
		-200...0	0.07 °C + 0.07% RDG	0.1 °C + 0.1% RDG
		0...400	0.07 °C	0.1 °C
U ⁽⁵⁾	-200...600	-200...0	0.07 °C + 0.05% RDG	0.1 °C + 0.07% RDG
		0...600	0.07 °C	0.1 °C
L ⁽⁵⁾	-200...900	-200...0	0.06 °C + 0.025% RDG	0.08 °C + 0.04% RDG
		0...900	0.06 °C + 0.002% RDG	0.08 °C + 0.005% RDG
C ⁽⁶⁾	0...2315	0...1000	0.22 °C	0.3 °C
		1000...2315	0.018% RDG	0.027% RDG
G ⁽⁷⁾	0...2315	0...60	⁽⁸⁾	⁽⁴⁾
		60...200	0.9 °C	1.0 °C
		200...400	0.4 °C	0.5 °C
		400...1500	0.2 °C	0.3 °C
		1500...2315	0.014% RDG	0.02% RDG
D ⁽⁶⁾	0...2315	0...140	0.3 °C	0.4 °C
		140...1200	0.2 °C	0.3 °C
		1200...2100	0.016% RDG	0.024% RDG
		2100...2315	0.45 °C	0.65 °C

Resolution 0.01 °C.

With internal reference junction please see separate specification.

Also other thermocouple types available as option, please contact Beamex.

¹⁾ Accuracy includes hysteresis, nonlinearity and repeatability (k=2).

²⁾ Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long term stability for mentioned period (k=2).

³⁾ IEC 584, NIST MN 175, BS 4937, ANSI MC96.1

⁴⁾ ±0.007% of thermovoltage + 4 µV

⁵⁾ DIN 43710

⁶⁾ ASTM E 988 - 96

⁷⁾ ASTM E 1751 - 95e1

⁸⁾ ±0.004% of thermovoltage + 3 µV

Measurement input impedance	> 10 MΩ
Simulation maximum load current	5 mA
Simulation load effect	< 5 µV/mA
Supported units	°C, °F, Kelvin, °Ré, °Ra
Connector	TC1: Universal TC connector , TC2: TC Miniplug

RTD MEASUREMENT & SIMULATION

R1 & R2 measurement

SENSOR TYPE	RANGE (°C)	RANGE (°C)	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY (±) ⁽²⁾
Pt50(385)	-200...850	-200...270 270...850	0.025 °C 0.009% RDG	0.03 °C 0.012% RDG
Pt100(375) Pt100(385) Pt100(389) Pt100(391) Pt100(3926)	-200...850	-200...0 0...850	0.011 °C 0.011 °C + 0.009% RDG	0.015 °C 0.015 °C + 0.012% RDG
Pt100(3923)	-200...600	-200...0 0...600	0.011 °C 0.011 °C + 0.009% RDG	0.015 °C 0.015 °C + 0.012% RDG
Pt200(385)	-200...850	-200...-80 -80...0 0...260 260...850	0.007 °C 0.016 °C 0.016 °C + 0.009% RDG 0.03 °C + 0.011% RDG	0.01 °C 0.02 °C 0.02 °C + 0.012% RDG 0.045 °C + 0.02% RDG
Pt400(385)	-200...850	-200...-100 -100...0 0...850	0.007 °C 0.015 °C 0.026 °C + 0.01% RDG	0.01 °C 0.02 °C 0.045 °C + 0.019% RDG
Pt500(385)	-200...850	-200...-120 -120...-50 -50...0 0...850	0.008 °C 0.013 °C 0.025 °C 0.025 °C + 0.01% RDG	0.01 °C 0.02 °C 0.045 °C 0.045 °C + 0.019% RDG
Pt1000(385)	-200...850	-200...-150 -150...-50 -50...0 0...850	0.007 °C 0.018 °C 0.022 °C 0.022 °C + 0.01% RDG	0.008 °C 0.03 °C 0.04 °C 0.04 °C + 0.019% RDG
Ni100(618)	-60...180	-60...0 0...180	0.009 °C 0.009 °C + 0.005% RDG	0.012 °C 0.012 °C + 0.006% RDG
Ni120(672)	-80...260	-80...0 0...260	0.009 °C 0.009 °C + 0.005% RDG	0.012 °C 0.012 °C + 0.006% RDG
Cu10(427)	-200...260	-200...260	0.012 °C	0.16 °C

32

R1 Simulation

SENSOR TYPE	RANGE (°C)	RANGE (°C)	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY (±) ⁽²⁾
Pt50(385)	-200...850	-200...270 270...850	0.055 °C 0.035 °C + 0.008% RDG	0.11 °C 0.11 °C + 0.015% RDG
Pt100(375) Pt100(385) Pt100(389) Pt100(391) Pt100(3926)	-200...850	-200...0 0...850	0.025 °C 0.025 °C + 0.007% RDG	0.05 °C 0.05 °C + 0.014% RDG
Pt100(3923)	-200...600	-200...0 0...600	0.025 °C 0.025 °C + 0.007% RDG	0.05 °C 0.05 °C + 0.014% RDG
Pt200(385)	-200...850	-200...-80 -80...0 0...260 260...850	0.012 °C 0.02 °C 0.02 °C + 0.006% RDG 0.03 °C + 0.011% RDG	0.025 °C 0.035 °C 0.04 °C + 0.011% RDG 0.06 °C + 0.02% RDG
Pt400(385)	-200...850	-200...-100 -100...0 0...850	0.01 °C 0.015 °C 0.027 °C + 0.01% RDG	0.015 °C 0.03 °C 0.05 °C + 0.019% RDG
Pt500(385)	-200...850	-200...-120 -120...-50 -50...0 0...850	0.008 °C 0.012 °C 0.026 °C 0.026 °C + 0.01% RDG	0.015 °C 0.025 °C 0.05 °C 0.05 °C + 0.019% RDG
Pt1000(385)	-200...850	-200...-150 -150...-50 -50...0 0...850	0.006 °C 0.017 °C 0.023 °C 0.023 °C + 0.01% RDG	0.011 °C 0.03 °C 0.043 °C 0.043 °C + 0.019% RDG
Ni100(618)	-60...180	-60...0 0...180	0.021 °C 0.019 °C	0.042 °C 0.037 °C + 0.001% RDG
Ni120(672)	-80...260	-80...0 0...260	0.021 °C 0.019 °C	0.042 °C 0.037 °C + 0.001% RDG
Cu10(427)	-200...260	-200...260	0.26 °C	0.52 °C

For platinum sensors Callendar van Dusen coefficients can be programmed. Also other RTD types available as option, please contact Beamex.

FEATURE	SPECIFICATION
RTD Measurement current	Pulsed, bi-directional 1 mA (0..500 Ω), 0.2 mA (>500 Ω)
4-wire connection	Measurement specifications valid
3-wire measurement	Add 10 mΩ
Max resistance excitation current	5 mA (0...650 Ω). I _{exc} * R _{sim} < 3.25 V (650...4000 Ω)
Min resistance excitation current	> 0.2 mA (0...400 Ω). >0.1 mA (400...4000 Ω)
Simulation settling time with pulsed excitation current	< 1 ms
Supported units	°C, °F, Kelvin, °Ré, °Ra

Internal reference junction TC1 & TC2

RANGE (°C)	ACCURACY ¹	1 YEAR UNCERTAINTY ²
-10...45 °C	±0.10 °C	±0.15 °C

Specifications valid in temperature range: 15...35 °C.

Temperature coefficient outside of 15...35 °C: ±0.005 °C/ °C.

Specifications assumes that calibrator has stabilized in environmental condition, being switched on, for minimum of 90 minutes. For a measurement or simulation done sooner than that, please add uncertainty of 0.15 °C.

In order to calculate the total uncertainty of thermocouple measurement or simulation with internal reference junction used, please add the relevant thermocouple uncertainty and the uncertainty together as a root sum of the squares.

VOLTAGE MEASUREMENT

IN (-1...60 V)

RANGE	RESOLUTION	ACCURACY ¹	1 YEAR UNCERTAINTY ²
-1.01...1 V	0.001 mV	3 μV + 0.003% RDG	5 μV + 0.006% RDG
1...60.6 V	0.01 mV	0.125 mV + 0.003% RDG	0.25 mV + 0.006% RDG
Input impedance		> 2 MΩ	
Supported units		V, mV, μV	

TC1 & TC2 (-1...1 V)

RANGE	RESOLUTION	ACCURACY ¹	1 YEAR UNCERTAINTY ²
-1.01...1.01 V	0.001 mV	3 μV + 0.004% RDG	4 μV + 0.007% RDG
Input impedance		> 10 MΩ	
Supported units		V, mV, μV	
Connector		TC1: Universal TC connector , TC2: TC Miniplug	

¹ Accuracy includes hysteresis, nonlinearity and repeatability (k=2).

² Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long term stability for mentioned period (k=2).

VOLTAGE GENERATION

OUT (-3...24 V)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
-3...10 V	0.00001 V	0.05 mV + 0.004% RDG	0.1 mV + 0.007% RDG
10...24 V	0.0001 V	0.05 mV + 0.004% RDG	0.1 mV + 0.007% RDG
Maximum load current		10 mA	
Short circuit current		>100 mA	
Load effect		< 50 μ V/mA	
Supported units		V, mV, μ V	

TC1 (-1...1 V)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
-1...1 V	0.001 mV	3 μ V + 0.004% RDG	4 μ V + 0.007% RDG
Maximum load current		5 mA	
Load effect		< 5 μ V/mA	
Supported units		V, mV, μ V	

34

CURRENT MEASUREMENT

IN (-100...100 mA)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
-25...25 mA	0.0001 mA	0.75 μ A + 0.0075% RDG	1 μ A + 0.01% RDG
\pm (25...101 mA)	0.001 mA	0.75 μ A + 0.0075% RDG	1 μ A + 0.01% RDG
Input impedance		< 10 Ω	
Supported units		mA, μ A	
Loop supply		Internal 24 V \pm 10% (max 55 mA), or external max 60 VDC	

CURRENT GENERATION

OUT (0...55 mA)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
0...25 mA	0.0001 mA	0.75 μ A + 0.0075% RDG	1 μ A + 0.01% RDG
25...55 mA	0.001 mA	1.5 μ A + 0.0075% RDG	2 μ A + 0.01% RDG
Internal loop supply		24 V \pm 5%. Max 55 mA.	
Max load impedance w. internal supply		24 V / (generated current). 1140 Ω @ 20 mA, 450 Ω @ 50 mA	
Max external loop supply		60 VDC	
Supported units		mA, μ A	

¹⁾ Accuracy includes hysteresis, nonlinearity and repeatability (k=2).

²⁾ Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long term stability for mentioned period (k=2).

FREQUENCY MEASUREMENT

IN (0.0027...51000 Hz)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
0.0027...0.5 Hz	0.000001 Hz	0.000002 Hz + 0.001% RDG	0.000002 Hz + 0.002% RDG
0.5...5 Hz	0.00001 Hz	0.00002 Hz + 0.001% RDG	0.00002 Hz + 0.002% RDG
5...50 Hz	0.0001 Hz	0.0002 Hz + 0.001% RDG	0.0002 Hz + 0.002% RDG
50...500 Hz	0.001 Hz	0.002 Hz + 0.001% RDG	0.002 Hz + 0.002% RDG
500...5000 Hz	0.01 Hz	0.02 Hz + 0.001% RDG	0.02 Hz + 0.002% RDG
5000...51000 Hz	0.1 Hz	0.2 Hz + 0.001% RDG	0.2 Hz + 0.002% RDG
Input impedance		>1 MΩ	
Supported units		Hz, kHz, cph, cpm, 1/Hz(s), 1/kHz(ms), 1/MHz(μs)	
Trigger level		Dry contact, wet contact -1...14 V	
Minimum signal amplitude		1.0 Vpp (<10kHz), 1.2 Vpp (10...50 kHz)	

FREQUENCY GENERATION

OUT (0.0005...50000 Hz)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
0.0005...0.5 Hz	0.000001 Hz	0.000002 Hz + 0.001% RDG	0.000002 Hz + 0.002% RDG
0.5...5 Hz	0.00001 Hz	0.00002 Hz + 0.001% RDG	0.00002 Hz + 0.002% RDG
5...50 Hz	0.0001 Hz	0.0002 Hz + 0.001% RDG	0.0002 Hz + 0.002% RDG
50...500 Hz	0.001 Hz	0.002 Hz + 0.001% RDG	0.002 Hz + 0.002% RDG
500...5000 Hz	0.01 Hz	0.02 Hz + 0.001% RDG	0.02 Hz + 0.002% RDG
5000...50000 Hz	0.1 Hz	0.2 Hz + 0.001% RDG	0.2 Hz + 0.002% RDG
Maximum load current		10 mA	
Wave forms		Positive square, symmetric square	
Output amplitude positive square wave		0...24 Vpp	
Output amplitude symmetric square wave		0...6 Vpp	
Duty Cycle		1...99%	
Amplitude accuracy		< 5% of amplitude	
Supported units		Hz, kHz, cph, cpm, 1/Hz(s), 1/kHz(ms), 1/MHz(μs)	

35

PULSE COUNTING

IN (0...9 999 999 pulses)

FEATURE	SPECIFICATION
Input impedance	>1 MΩ
Trigger level	Dry contact, wet contact -1...14 V
Minimum signal amplitude	1 Vpp (< 10 kHz), 1.2 Vpp (10...50 kHz)
Max frequency	50 kHz
Trigger edge	Rising, falling

¹⁾ Accuracy includes hysteresis, nonlinearity and repeatability (k=2).

²⁾ Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long term stability for mentioned period (k=2).

PULSE GENERATION

OUT (0...9 999 999 pulses)

FEATURE	SPECIFICATION
Resolution	1 pulse
Maximum load current	10 mA
Output amplitude positive pulse	0...24 Vpp
Output amplitude symmetric pulse	0...6 Vpp
Pulse frequency range	0.0005...10000 Hz
Duty cycle	1...99%

RESISTANCE MEASUREMENT

R1 & R2 (0...4000 Ω)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
-1...100 Ω	0.001 Ω	4.5 mΩ	6 mΩ
100...110 Ω	0.001 Ω	0.0045% RDG	0.006% RDG
110...150 Ω	0.001 Ω	0.005% RDG	0.007% RDG
150...300 Ω	0.001 Ω	0.006% RDG	0.008% RDG
300...400 Ω	0.001 Ω	0.007% RDG	0.009% RDG
400...4040 Ω	0.01 Ω	9 mΩ + 0.008% RDG	12 mΩ + 0.015% RDG

Measurement current	Pulsed, bi-directional 1 mA (0..500 Ω), 0.2 mA (>500 Ω)
Supported units	Ω, kΩ
4-wire connection	Measurement specifications valid
3-wire measurement	Add 10 mΩ

RESISTANCE SIMULATION

R1 (0...4000 Ω)

RANGE	RESOLUTION	ACCURACY ⁽¹⁾	1 YEAR UNCERTAINTY ⁽²⁾
0...100 Ω	0.001 Ω	10 mΩ	20 mΩ
100...400 Ω	0.001 Ω	5 mΩ + 0.005% RDG	10 mΩ + 0.01% RDG
400...4000 Ω	0.01 Ω	10 mΩ + 0.008% RDG	20 mΩ + 0.015% RDG

Max resistance excitation current	5 mA (0...650 Ω). I _{exc} * R _{sim} < 3.25 V (650...4000 Ω)
Min resistance excitation current	> 0.2 mA (0...400 Ω). >0.1 mA (400...4000 Ω)
Settling time with pulsed excitation current	< 1ms
Supported units	Ω, kΩ

¹⁾ Accuracy includes hysteresis, nonlinearity and repeatability (k=2).

²⁾ Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long term stability for mentioned period (k=2).

Modularity, options and accessories

MODULARITY AND OPTIONS

- All electrical / temperature functions are included as standard
- Two case bottom choices:
 - flat (no room for internal pressure modules, only barometer)
 - extended (room for internal pressure modules)
- Optional internal pressure modules (up to four internal pressure modules; three standard and one barometric)
- Optional user-interface modes:
 - Documenting calibrator
 - Data logger
 - HART communicator
 - FOUNDATION Fieldbus communicator
 - Profibus PA communicator
- Pressure / temperature controller communications



37

STANDARD ACCESSORIES

- Accredited calibration certificate
- User guide
- Computer cable (USB)
- Battery charger / eliminator
- Internal LiPO battery pack
- Test leads and clips
- Appropriate pressure T-hose with internal low pressure modules
- CD-ROM with user manual, software tools and product information



OPTIONAL ACCESSORIES

- Soft carrying case
- Soft accessory case
- Hard carrying case
- Spare battery pack
- Adapter cables for the second RTD channel
- Cable for pressure and temperature controllers



Beamex MC6

ADVANCED FIELD CALIBRATOR AND COMMUNICATOR

38

Beamex MC6 is an advanced, high-accuracy field calibrator and communicator. It offers calibration capabilities for pressure, temperature and various electrical signals. The MC6 also contains a full fieldbus communicator for HART, FOUNDATION Fieldbus and Profibus PA instruments. The MC6 is one device with five different operational modes, which means that it is fast and easy to use, and you can carry less equipment in the field. The operation modes are: meter, calibrator, documenting calibrator, data logger and fieldbus communicator. In addition, the MC6 communicates with Beamex CMX calibration software, enabling fully automated and paperless calibration and documentation.

Guided procedures

The MC6 provides automated, guided procedures. For instance, whenever a certain measurement or generation is selected, the user interface shows where to make the connections.

Paperless calibration

The MC6 communicates with calibration software enabling fully automated and paperless calibration and documentation.

One device, five operational modes

How is it possible to combine advanced functionality with ease-of-use? In the MC6 this has been achieved through integrating various operational modes into one device. This means that you only need to learn how to use one device.

Communicator

Smart instrumentation is becoming more and more common in today's process plants. The most widely used smart instrument protocols are HART, FOUNDATION Fieldbus and Profibus PA. Therefore, in addition to a calibrator, an engineer often needs to use a field communicator. The MC6 combines these two; it's a calibrator and a communicator.



Main features

- ▶ High-accuracy calibrator for pressure, temperature and electrical signals
- ▶ Full multi-bus communicator for HART, FOUNDATION Fieldbus and Profibus PA instruments
- ▶ Five operational modes: meter, calibrator, documenting calibrator, data logger and communicator
- ▶ Combines advanced functionality with ease-of-use
- ▶ Automates calibration procedures for paperless calibration management



Beamex MC4


DOCUMENTING PROCESS CALIBRATOR



Document as you go



780773487588347338843
11798865495495495
780773487588347338843
525879558838458734657
58554875733884534900



MC4: a compact, easy-to-use documenting process calibrator

The Beamex MC4 is a documenting process calibrator. Instrument data can be sent from a computer to the MC4 and calibration results can be uploaded from the MC4 to a computer containing the Beamex CMX calibration software. Being a multifunctional calibrator, the MC4 is suitable for calibrating various process parameters, such as pressure, temperature and electrical signals.

High accuracy is one of the important features of the MC4. A standard feature of the MC4 includes an accredited calibration certificate as proof of its accuracy. The correction coefficients of a PRT probe can be programmed into the MC4 to further improve temperature accuracy. The large graphical display, menu-based multilingual user interface and full numerical keyboard make it easy to use.



Main features of MC4

Communication with calibration software

Using the MC4 together with a calibration software provides you with a complete documenting calibration system that produces calibration certificates automatically.

All-in-one functionality

The MC4 is a versatile calibrator with many different functions. There's no need to take several different measurement devices to the field – the MC4 does the job.

Accuracy guaranteed

The MC4 is a highly accurate process calibrator. As a proof of this, each calibrator is delivered with a traceable, accredited calibration certificate.

Calibration is quick and easy

The large graphical display, menu-based multilingual user interface and full numerical keyboard make the MC4 quick and easy to use.



Advanced features of MC4

FEATURE	SPECIFICATION
Calibration mode	The MC4 includes a versatile calibration mode making it easy and effective to create and calibrate process instruments.
PRT sensor coefficients	The MC4 compensates sensor errors because it includes the possibility to record PRT sensor correction coefficients.
Error% display	When calibrating a transmitter, its output may be displayed in an error% unit rather than in an engineering unit.
Error display in input or output units	When calibrating a transmitter, the transmitter's output may be displayed as an error in input or output engineering units.
% display	Any measurement or generation may be presented in percentages within the user-programmable range.
Scaling	A versatile, programmable scaling function allows the user to scale any measured or generated unit into any custom unit. Scaling also includes a rooting transfer function for flow applications as well as custom transfer functions.
User setups	The unit has a large number of user-configurable setups that make it easy to save and quickly recall a desired configuration.
Leak testing	The leak test function indicates pressure drops and leak rates during the user-programmable period.
Step and ramp	The unit includes a versatile and programmable automatic step and ramp function as well as a manual step function.
Programmable alarms	An alarm based on a measurement value or rate of change can be programmed into the device.
Damping	Programmable damping allows the user to select different filters for measurements.
Bar graph	The bar graph allows the user to display a measurement or generation as an analogue bar, including programmable starting and ending points.
Difference	Difference measurement allows the user to measure the difference between two pressure modules.
Deviation	The deviation function allows the user to display a deviation between a given reference value and the actual measurement.
Redundancy	Redundancy measurement allows the user to measure the same pressure using two pressure modules (internal and external) simultaneously. The unit's alarm sounds if the readings excessively differ from each other.
Additional information	The unit also allows the user to view additional information such as min, max, rate, internal temperature, thermocouple's thermovoltage, RTD sensor's resistance etc.

General specifications

FEATURE	SPECIFICATION
Display	60 mm x 60 mm (2.36" x 2.36"), 160 x 160 pixels, back lit LCD
Weight	720...830 g (1.59...1.83 lbs)
Dimensions	215 mm (8.5") x 102 mm (4") x 49 mm (1.9") (d/w/h)
Keyboard	Membrane keyboard
Battery type	Rechargeable NiMH pack, 4000 mAh, 3.6V DC
Charging time	5 hours
Charger supply	100...240 VAC, 50–60 Hz
Battery operation	13...24 hours in measurement mode, back light off. 8...12 hours when sourcing an average of 12 mA to loop, with back light on.
Battery operation with optional dry battery cartridge and 4 alkaline AA cells	4...8 hours in measurement mode, back light off. 3...4 hours when sourcing an average of 12 mA to loop, with back light on.
Operating temperature	-10...50 °C (14...122°F)
Operating temp. while charging batteries	0...35 °C (32...95°F)
Storage temperature	-20...60 °C (-4...140°F)
Humidity	0 to 80% R.H. non-condensing
Warm-up time	Specifications valid after a 5-minute warm-up period.
Max. input voltage	30 V AC, 60 V DC
Safety	Directive 73/23/EEC, EN 61010-1
EMC	Directive 89/336/EEC, EN 61326

VOLTAGE MEASUREMENT -1 ... 60 V DC

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ¹⁾
±0.25 V	0.001mV	0.02% RDG + 5 µV
±(0.25...1 V)	0.01 mV	0.02% RDG + 5 µV
1...25 V	0.1 mV	0.02% RDG + 0.25 mV
25...60 V	1 mV	0.02% RDG + 0.25 mV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	>1 MΩ
Supported units	V, mV, µV
Display update rate	3 / second

mA MEASUREMENT ±100 mA

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ¹⁾
±25mA	0.0001 mA	0.02% RDG + 1.5 µA
±(25...100 mA)	0.001 mA	0.02% RDG + 1.5 µA

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	< 7.5 Ω
Supported units	mA, µA
Display update rate	3 / second

LOOP SUPPLY

FEATURE	SPECIFICATION
Maximum output current	> 25 mA, short circuit protected
Output voltage	24 V ±10%
Output impedance in HART compatible mode	300 Ω ±20%

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

Electrical measurements

FREQUENCY MEASUREMENT 0.0027...50 000 Hz

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ¹⁾
0.0027...0.5 Hz	0.000001 Hz	0.01% RDG
0.5...5 Hz	0.00001 Hz	0.01% RDG
5...50 Hz	0.0001 Hz	0.01% RDG
50...500 Hz	0.001 Hz	0.01% RDG
500...5000 Hz	0.01 Hz	0.01% RDG
5000...50000 Hz	0.1 Hz	0.01% RDG

FEATURE	SPECIFICATION
Temperature coefficient	Specification valid from -10 to 50 °C (14...122°F)
Input impedance	> 1 M Ω
Trigger level	-1...14 V in 1 V steps and open collector inputs
Minimum signal amplitude	2 Vpp (< 10 kHz), 3 Vpp (10...50 kHz)
Supported units	Hz, kHz, cph, cpm, 1/Hz (s), 1/kHz (ms), 1/MHz (μ s)
Gate period	267 ms + 1 signal period

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

44

PULSE COUNTING 0...9 999 999 PULSES

FEATURE	SPECIFICATION
Range	0 to 9 999 999 pulses
Input impedance	> 1 M Ω
Trigger level	-1...14 V in 1 V steps and open collector inputs
Minimum signal amplitude	2 Vpp (pulse length > 50 μ s), 3 Vpp (pulse length 10...50 μ s)

SWITCH TEST

FEATURE	SPECIFICATION	
Potential free contacts	Test voltage (trigger level)	3 V, 0.13 mA (1 V) or 24 V, 35 mA (2 V)
Voltage level detection	Trigger level	-1...14 V in 1 V steps
	Input impedance	> 1 M Ω

Pressure measurements

INTERNAL PRESSURE MODULES (NPM)

INTERNAL MODULE ³⁾	UNIT	RANGE ²⁾	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ¹⁾
NPM200mC	kPa	± 20	0.001	0.035% FS + 0.05% RDG
	mbar	± 200	0.01	
	iwc	± 80	0.001	
NPM2C	kPa	-100 to 200	0.001	0.015% FS + 0.035% RDG
	bar	-1 to 2	0.00001	
	psi	-14.5 to 30	0.001	
NPM20C	kPa	-100 to 2000	0.01	0.015% FS + 0.035% RDG
	bar	-1 to 20	0.0001	
	psi	-14.5 to 300	0.01	
NPM160	MPa	0...16	0.0001	0.015% FS + 0.035% RDG
	bar	0...160	0.001	
	psi	0...2400	0.01	
Barometric option	Also enables absolute pressure measurement for the above pressure inputs. When using the barometric option, add 0.1 kPa (0.0146 psi) uncertainty for absolute pressure measurement.			

FEATURE	SPECIFICATION
Temperature coefficient	< $\pm 0.001\%$ RDG / °C outside 15...35 °C < $\pm 0.0006\%$ RDG / °F outside 59...95 °F
Maximum overpressure	2 x Range
Pressure port	G 1/8" female with G 1/8" male (ISO 228/1) 60° internal cone adapter NPM160: G 1/8" female
Media compatibility	Wetted parts: AISI316 stainless steel, Nitrile rubber.
Supported pressure units	Pa, hPa, kPa, MPa, mbar, bar, lbf/ft ² , psi, ozf/in ² , gf/cm ² , kgf/cm ² , kgf/m ² , kp/cm ² , at, mmH ₂ O, cmH ₂ O, mH ₂ O, iwc, ftH ₂ O, mmHg, cmHg, mHg, inHg, mmHg(0 °C), inHg(0 °C), mmH ₂ O(4 °C; 60°F; 68°F/20 °C), cmH ₂ O(4 °C; 60°F; 68°F/20 °C), inH ₂ O(4 °C; 60°F; 68°F/20 °C), ftH ₂ O(4 °C; 60°F; 68°F/20 °C), torr, atm, + four (4) user-configurable units
Display update rate	2.5 / second

45

EXTERNAL PRESSURE MODULES (EXT) STANDARD ACCURACY

EXTERNAL MODULE	RANGE ²⁾	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ¹⁾
EXT200mC-s	± 200 mbar	± 80 iwc 0.01 mbar 0.01 iwc	0.05% RDG + 0.05% FS
EXT2C-s	-1...2 bar	-14.5...30 psi 0.0001 bar 0.001 psi	0.05% FS
EXT20C-s	-1...20 bar	-14.5...300 psi 0.001 bar 0.01 psi	0.05% FS
EXT160-s	0...160 bar	0...2400 psi 0.01 bar 0.1 psi	0.05% FS

EXTERNAL PRESSURE MODULES (EXT) HIGH ACCURACY

MODULE	RANGE ²⁾	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ¹⁾
Barometric	800...1200 mbar abs	23.6...35.4 inHg a	0.5 mbar (0.015 inHg)
EXT10mD	± 10 mbar differential	± 4 iwc differential	0.05% Span + 0.1% RDG
EXT100m	0...100 mbar gauge	0...40 iwc	0.025% FS + 0.025% RDG
EXT400mC	± 400 mbar	± 160 iwc	0.02% FS + 0.025% RDG
EXT1C	± 1 bar	-14.5...15 psi	0.015% FS + 0.025% RDG
EXT2C	-1...2 bar	-14.5...30 psi	0.01% FS + 0.025% RDG
EXT6C	-1...6 bar	-14.5...90 psi	0.01% FS + 0.025% RDG
EXT20C	-1...20 bar	-14.5...300 psi	0.01% FS + 0.025% RDG
EXT60	0...60 bar	0...900 psi	0.01% FS + 0.025% RDG
EXT100	0...100 bar	0...1500 psi	0.01% FS + 0.025% RDG
EXT160	0...160 bar	0...2400 psi	0.01% FS + 0.025% RDG
EXT250	0...250 bar	0...3700 psi	0.015% FS + 0.025% RDG
EXT600	0...600 bar	0...9000 psi	0.015% FS + 0.025% RDG
EXT1000	0...1000 bar	0...15000 psi	0.015% FS + 0.025% RDG

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

2) The internal pressure module's range may also be displayed in absolute pressure if a barometric module is used.

3) The MC4 calibrator can hold one internal pressure module and the barometric option.

All external pressure modules (EXT) are also compatible with Beamex MC2, MC5, MC5P and MC6 calibrators.

mV MEASUREMENT (T/C-TERMINALS) –25... 150 mV

RANGE	RESOLUTION	1 YEAR UNCERTAINTY(±) ¹⁾
–25... 150 mV	0.001 mV	0.02% RDG + 4 µV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	> 10 MΩ
Supported units	V, mV, µV
Display update rate	3 / second

mV GENERATION (T/C-TERMINALS) –25... 150 mV

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ¹⁾
–25... 150 mV	0.001 mV	0.02% RDG + 4 µV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Maximum load current	5 mA
Load effect	< 5µV/mA
Supported units	V, mV, µV

46

VOLTAGE GENERATION –3... 12 V

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ¹⁾
±0.25 V	0.01 mV	0.02% RDG + 0.1 mV
–3...–0.25 V	0.1 mV	0.02% RDG + 0.1 mV
0.25... 12 V	0.1 mV	0.02% RDG + 0.1 mV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Maximum load current	5 mA
Load effect	< 50 µV/mA
Supported units	V, mV, µV

mA GENERATION (SOURCE/SINK) 0... 25 mA

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ¹⁾
0... 25 mA	0.0001 mA	0.02% RDG + 1.5 µA

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Max load impedance (source)	750 Ω (0...20 mA), 600 Ω (20...25 mA)
Max loop voltage (sink)	60 V
Supported units	mA, µA

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

RESISTANCE MEASUREMENT 0...4000 Ω

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0...250 Ω	1 mΩ	4-wire connection: 0.02% RDG + 3.5 mΩ 3-wire connection: 0.02% RDG + 13.5 mΩ
250...2650 Ω	10 mΩ	
2650...4000 Ω	100 mΩ	

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Measurement current	Pulsed, bi-directional 1 mA (0...500 Ω), 0.2 mA (>500 Ω)
Supported units	Ω, kΩ
Display update rate	3 / second

RESISTANCE SIMULATION 0...4000 Ω

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0...400 Ω	10 mΩ	0.04% RDG or 30 mΩ (whichever is greater)
400...4000 Ω	100 mΩ	0.04% RDG or 30 mΩ (whichever is greater)

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Maximum resistance excitation current	5 mA (0...650 Ω) $I_{exc} \times R_{sim} < 3.25 V$ (650...4000 Ω)
Settling time (pulsed currents)	1 ms
Supported units	Ω, kΩ

Specification valid with an excitation current >0.2 mA (0...400 ohm), >0.1 mA (400...4000 ohm).

FREQUENCY GENERATION 0.0005...10 000 Hz

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0.0005...0.5 Hz	0.000001 Hz	0.01% RDG
0.5...5 Hz	0.00001 Hz	0.01% RDG
5...50 Hz	0.0001 Hz	0.01% RDG
50...500 Hz	0.001 Hz	0.01% RDG
500...5000 Hz	0.01 Hz	0.01% RDG
5000...10000 Hz	0.1 Hz	0.01% RDG

FEATURE	SPECIFICATION
Temperature coefficient	Specification valid from -10 to 50 °C (14...122°F)
Maximum load current	5 mA
Output amplitude positive square wave	0...12 Vpp ±(0.2 V+5%)
Output amplitude symmetric square wave	0...6 Vpp ±(0.2 V+5%)
Duty cycle	1...99% (0.0009...500 Hz), high / low time: min 25µs, max 1165 s
Supported units	Hz, kHz, cph, cpm, 1/Hz (s), 1/kHz (ms), 1/MHz (µs)
Jitter	< 0.28 µs

PULSE GENERATION 0...9 999 999 PULSES

FEATURE	SPECIFICATION
Range	0 to 9 999 999 pulses
Resolution	1 pulse
Maximum load current	5 mA
Output amplitude positive pulse	0...12 Vpp ±(0.2 V+5%)
Output amplitude symmetric pulse	0...6 Vpp ±(0.2 V+5%)
Pulse frequency	0.0005...10 000 Hz
Duty cycle	1...99% (0.0009...500 Hz), high / low time: min 25µs, max 1165 s

⁽¹⁾ Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period. (k=2).

THERMOCOUPLE MEASUREMENT AND SIMULATION

Thermocouple types available as standard

TYPE	RANGE (°C)	RANGE (°C)	1 YEAR UNCERTAINTY (±) ¹⁾
B ²⁾	0...1820	0...200	³⁾
		200...500	2.0 °C
		500...800	0.8 °C
		800...1820	0.6 °C
R ²⁾	-50...1768	-50...0	1.0 °C
		0...50	0.7 °C
		50...1400	0.5 °C
		1400...1768	0.6 °C
S ²⁾	-50...1768	-50...0	1.0 °C
		0...50	0.7 °C
		50...1500	0.6 °C
		1500...1768	0.7 °C
E ²⁾	-270...1000	-270...-200	³⁾
		-200...0	0.07 °C + 0.08% RDG
		0...600	0.07 °C + 0.015% RDG
		600...1000	0.026% RDG
J ²⁾	-210...1200	-210...-200	³⁾
		-200...0	0.08 °C + 0.07% RDG
		0...1200	0.08 °C + 0.02% RDG
K ²⁾	-270...1372	-270...-200	³⁾
		-200...0	0.1 °C + 0.1% RDG
		0...1000	0.1 °C + 0.02% RDG
		1000...1372	0.03% RDG
N ²⁾	-270...1300	-270...-200	³⁾
		-200...-100	0.2% RDG
		-100...0	0.15 °C + 0.05% RDG
		0...750	0.15 °C + 0.01% RDG
		750...1300	0.03% RDG
T ²⁾	-270...400	-270...-250	³⁾
		-250...-200	0.7 °C
		-200...0	0.1 °C + 0.1% RDG
		0...400	0.1 °C + 0.01% RDG
U ⁴⁾	-200...600	-200...0	0.15 °C + 0.1% RDG
		0...600	0.15 °C + 0.01% RDG
L ⁴⁾	-200...900	-200...0	0.13 °C + 0.07% RDG
		0...900	0.13 °C + 0.02% RDG
C ⁵⁾	0...2315	0...900	0.4 °C
		900...2000	0.045% RDG
		2000...2315	1.2 °C
G ⁶⁾	0...2315	0...70	³⁾
		70...200	1.0 °C
		200...1600	0.5 °C
		1600...2000	0.7 °C
		2000...2315	1.0 °C
D ⁵⁾	0...2315	0...1000	0.4 °C
		1000...2000	0.04% RDG
		2000...2315	1.2 °C

FEATURE	MEASUREMENT	SIMULATION
Resolution	0.01 °C	0.01 °C
Temperature coefficient	< ±0.0015% of thermovoltage / °C outside of 18...28 °C < ±0.0008% of thermovoltage / °F outside of 64.4...82.4°F	< ±0.0015% of thermovoltage / °C outside of 18...28 °C < ±0.0008% of thermovoltage / °F outside of 64.4...82.4°F
Input impedance	>10 MΩ	–
Supported units	°C, °F, K	°C, °F, K
Display update rate	3 / second	–
Maximum load current	–	5 mA
Load effect	–	< 5 µV/mA

INTERNAL REFERENCE JUNCTION

RANGE (°C)	1 YEAR UNCERTAINTY
-10...50 °C	±0.25 °C

- 1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).
Uncertainty does not include reference junction uncertainty.
- 2) IEC 584, NIST MN 175, BS 4937, ANSI MC96.1
- 3) ±0.02% of thermovoltage + 4 µV
- 4) DIN 43710
- 5) ASTM E 988 - 96
- 6) ASTM E 1751 - 95e1

RTD MEASUREMENT AND SIMULATION

SENSOR TYPE	RANGE	RESOLUTION	MEASUREMENT 1 YEAR UNCERTAINTY (±) ¹⁾	SIMULATION 1 YEAR UNCERTAINTY (±) ^{1) 2)}
Pt 50...1000	-200...0 °C 0...850 °C	0.01 °C	0.06 °C 0.06 °C + 0.025% RDG	0.10 °C 0.10 °C + 0.025% RDG
Ni 100	-60...180 °C	0.01 °C	0.06 °C	0.12 °C
Ni 120	-80...260 °C	0.01 °C	0.06 °C	0.12 °C
Cu10	-200...260 °C	0.01 °C	0.2 °C	0.8 °C

FEATURE	MEASUREMENT	SIMULATION
Temperature coefficient	< ±0.0015% of resistance / °C outside of 18...28 °C < ±0.0008% of resistance / °F outside of 64.4...82.4°F	< ±0.0015% of resistance / °C outside of 18...28 °C < ±0.0008% of resistance / °F outside of 64.4...82.4°F
Measurement current	Pulsed, 1 mA (0..500 Ω), 0.2 mA (>500 Ω)	–
Maximum resistance excitation current	–	5 mA (0...650 Ω) I _{exc} × R _{sim} < 3.25 V (650...4000 Ω)
Supported units	°C, °F, K	°C, °F, K
Display update rate	3 / second	–
Settling time (pulsed currents)	1 ms	–

RTD TYPES AVAILABLE AS STANDARD

Pt50 (385)	Pt400 (385)	Pt100 (3926)	Pt100 (3923)	Cu10 (427)
Pt100 (385)	Pt500 (385)	Pt100 (391)	Ni100 (618)	
Pt200 (385)	Pt1000 (385)	Pt100 (375)	Ni120 (672)	

- 1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).
- 2) Specification valid with an excitation current >0.2 mA (0...400 Ω), >0.1 mA (400...4000 Ω).

MC4 supports Callendar van Dusen correction coefficients for PRT sensors to compensate sensor error.

STANDARD ACCESSORIES

- User guide
- Accredited calibration certificate
- Internal rechargeable NiMH battery pack + battery charger
- Test leads and clips
- USB cable
- Adapter pressure connector – from G1/8" female to G 1/8" male
with 60° internal cone (included in models with internal pressure module)

OPTIONAL ACCESSORIES

- Pressure T-hose
- Soft carrying case
- Connection cable for external pressure modules
- Dry battery cartridge
- Calibration hand-pumps

Beamex MC4

DOCUMENTING PROCESS CALIBRATOR

50

The Beamex MC4 is a documenting process calibrator. Instrument data can be sent from a computer to the MC4, and calibration results can be uploaded from the MC4 to a computer using the Beamex CMX calibration software. Being a multifunctional calibrator, the MC4 is suitable for calibrating various process parameters, such as pressure, temperature and electrical signals. High accuracy is one of the important features of the MC4. A standard feature of the MC4 includes an accredited calibration certificate as proof of its accuracy.

Communication with calibration software

Using the MC4 together with calibration software provides you with a complete documenting calibration system that produces calibration certificates automatically.

All-in-one functionality

The MC4 is a versatile calibrator with many different functions. There's no need to take several different measurement devices to the field – MC4 does the job.

Accuracy guaranteed

The MC4 is a highly accurate process calibrator. As a proof of this, each calibrator is delivered with a traceable, accredited calibration certificate.

Calibration is quick and easy

The large graphical display, menu-based multilingual user interface, and full numerical keyboard make the MC4 quick and easy to use.



Main features

- ▶ Automated and documented calibrations quickly and easily
- ▶ Calibration capabilities for pressure, temperature, electrical and frequency signals
- ▶ Compact size and design
- ▶ Documenting – communicates with Beamex calibration software



Beamex MC2

HAND-HELD CALIBRATOR



Practicality in calibration

730773487588347338843
11796865495495495
730773487588347338843
5238799558138458734657
505348757338848534900



MC2 series: three different hand-held calibrators for field use

Practicality in calibration. The Beamex MC2 series includes three different hand-held calibrators for field use: the MC2 temperature/electrical calibrator and the MC2 multifunction calibrator. The MC2 is a compact and easy-to-use hand-held calibrator. It has a large graphical display, a menu-based interface and a full numerical keyboard. The MC2 represents the high, uncompromised quality standards of Beamex calibration equipment.

53

The main features of MC2

Compact and user-friendly

The MC2 is a compact, lightweight portable calibrator with large graphical display, multilingual interface and full numerical keyboard. Calibration is quick and simple.

Accuracy guaranteed

The MC2 is delivered with a traceable, accredited calibration certificate.

Safe and robust field calibrator

The MC2 with impact protectors and membrane keyboard is robust and made for tough use.

Wide range of configuration possibilities

The MC2 provides a number of configuration possibilities, such as internal and external pressure modules.



The MC2 series specifications



54

FEATURES	MC2-TE TEMPERATURE / ELECTRICAL	MC2-MF MULTIFUNCTION
Internal pressure module	–	●
Connection for external pressure modules	●	●
Current measurement (with internal and external supply)	●	●
Voltage measurement	●	●
Frequency measurement	●	●
Pulse counting	●	●
Switch sensing	●	●
Internal HART compatible 24 VDC loop supply	●	●
Current generation (with internal and external supply)	●	●
Voltage generation	●	●
Frequency generation	●	●
Pulse generation	●	●
mV measurement / simulation	●	●
Resistance measurement / simulation	●	●
RTD measurement / simulation	●	●
TC measurement / simulation	●	●

The MC2 general specifications

GENERAL SPECIFICATIONS

GENERAL	MC2
Display	60 mm x 60 mm (2.36" x 2.36"), 160 x 160 pixels backlit LCD
Weight	720...830 g (1.59...1.83 lbs)
Dimensions	215 mm (8.5") x 102 mm (4") x 49 mm (1.9") (d/w/h)
Keyboard	Membrane keyboard
Battery type	Rechargeable NiMH, 4000 mAh, 3.6V DC
Charging time	5 hours
Charger supply	100...240 VAC, 50-60 Hz
Battery operation	13...24 hours in measurement mode, back light off. 8...12 hours when sourcing an average of 12 mA to loop, with back light on.
Operating temperature	-10...50 °C (14...122°F)
Operating temperature when charging batteries	0...35 °C (32...95°F)
Storage temperature	-20 to 60 °C (-4 to 140°F)
Humidity	0 to 80% R.H. non condensing
Warmup time	Specifications valid after a 5 minute warmup period.
Max. input voltage	30 V AC, 60 V DC
Safety	Directive 73/23/EEC, EN 61010-1
EMC	Directive 89/336/EEC, EN 61326
Warranty	Standard: 2 years for MC2; 1 year for battery pack. ⁽¹⁾

1) Warranty extension programs are also available.

55

VOLTAGE MEASUREMENT -1...60 V DC

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
±0.25 V	0.001mV	0.02% RDG + 5 µV
±(0.25...1 V)	0.01 mV	0.02% RDG + 5 µV
1...25 V	0.1 mV	0.02% RDG + 0.25 mV
25...60 V	1 mV	0.02% RDG + 0.25 mV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	>1 MΩ
Supported units	V, mV, µV
Display update rate	3 / second

mA MEASUREMENT ±100 mA

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
±25mA	0.0001 mA	0.02% RDG + 1.5 µA
±(25...100 mA)	0.001 mA	0.02% RDG + 1.5 µA

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	< 7.5 Ω
Supported units	mA, µA
Display update rate	3 / second

LOOP SUPPLY

FEATURE	SPECIFICATION
Maximum output current	> 25 mA, short circuit protected
Output voltage	24 V ± 10%
Output impedance in HART compatible mode	300 Ω ± 20%

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

Electrical measurements

FREQUENCY MEASUREMENT 0.0027...50 000 Hz

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ¹⁾
0.0027...0.5 Hz	0.000001 Hz	0.01% RDG
0.5...5 Hz	0.00001 Hz	0.01% RDG
5...50 Hz	0.0001 Hz	0.01% RDG
50...500 Hz	0.001 Hz	0.01% RDG
500...5000 Hz	0.01 Hz	0.01% RDG
5000...50000 Hz	0.1 Hz	0.01% RDG

FEATURE	SPECIFICATION
Temperature coefficient	Specification valid from -10 to 50 °C (14...122°F)
Input impedance	> 1 M Ω
Trigger level	-1...14 V in 1 V steps and open collector inputs
Minimum signal amplitude	2 Vpp (< 10 kHz), 3 Vpp (10...50 kHz)
Supported units	Hz, kHz, cph, cpm, 1/Hz (s), 1/kHz (ms), 1/MHz (μ s)
Gate period	267 ms + 1 signal period

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

56

PULSE COUNTING 0...9 999 999 PULSES

FEATURE	SPECIFICATION
Range	0 to 9 999 999 pulses
Input impedance	> 1 M Ω
Trigger level	-1...14 V in 1 V steps and open collector inputs
Minimum signal amplitude	2 Vpp (pulse length > 50 μ s), 3 Vpp (pulse length 10...50 μ s)

SWITCH TEST

FEATURE	SPECIFICATION	MC2
Potential free contacts	Test voltage (trigger level)	3 V, 0.13 mA (1 V) or 24 V, 35 mA (2 V)
Voltage level detection	Trigger level Input impedance	-1...14 V in 1 V steps > 1 M Ω



Pressure measurement

INTERNAL PRESSURE MODULES (IPM)

INTERNAL MODULE ⁽³⁾	UNIT	RANGE ⁽²⁾	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
IPM200mC	kPa	± 20	0.001	0.05% RDG + 0.05% FS
	mbar	± 200	0.01	
	iwc	± 80	0.01	
IPM2C	kPa	-100 to 200	0.01	0.05% FS
	bar	-1 to 2	0.0001	
	psi	-14.5 to 30	0.001	
IPM20C	kPa	-100 to 2000	0.1	0.05% FS
	bar	-1 to 20	0.001	
	psi	-14.5 to 300	0.01	
IPM160	MPa	0...16	0.001	0.05% FS
	bar	0...160	0.01	
	psi	0...2400	0.1	
Barometric option	Also enables absolute pressure measurement for the above pressure inputs. When using the barometric option, add 0.1 kPa (0.0146 psi) uncertainty for absolute pressure measurement.			

FEATURE	SPECIFICATION
Temperature coefficient	< $\pm 0.001\%$ RDG / °C outside 15...35 °C. < $\pm 0.0006\%$ RDG / °F outside 59...95°F
Maximum overpressure	2 \times Range
Pressure port	G 1/8" female with G 1/8" male (ISO 228/1) 60° internal cone adapter IPM160: G 1/8" female
Media compatibility	Wetted parts: AISI316 stainless steel, Nitrile rubber
Supported pressure units	Pa, hPa, kPa, MPa, mbar, bar, lbf/ft ² , psi, ozf/in ² , gf/cm ² , kgf/cm ² , kgf/m ² , kp/cm ² , at, mmH ₂ O, cmH ₂ O, mH ₂ O, iwc, ftH ₂ O, mmHg, cmHg, mHg, inHg, mmHg(0 °C), inHg(0 °C), mmH ₂ O(4 °C; 60°F; 68°F/20 °C), cmH ₂ O(4 °C; 60°F; 68°F/20 °C), inH ₂ O(4 °C; 60°F; 68°F/20 °C), ftH ₂ O(4 °C; 60°F; 68°F/20 °C), torr, atm, + four (4) user-configurable units
Display update rate	2.5 / second

57

EXTERNAL PRESSURE MODULES (EXT) STANDARD ACCURACY

MODULE	RANGE ⁽²⁾	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
EXT200mC-s	± 200 mbar	± 80 iwc 0.01 mbar 0.01 iwc	0.05% RDG + 0.05% FS
EXT2C-s	-1...2 bar	-14.5...30 psi 0.0001 bar 0.001 psi	0.05% FS
EXT20C-s	-1...20 bar	-14.5...300 psi 0.001 bar 0.01 psi	0.05% FS
EXT160-s	0...160 bar	0...2400 psi 0.01 bar 0.1 psi	0.05% FS

EXTERNAL PRESSURE MODULES (EXT) HIGH ACCURACY

MODULE	RANGE ⁽²⁾	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
Barometric	800...1200 mbar abs 23.6...35.4 inHg a	0.5 mbar (0.015 inHg)
EXT10mD	± 10 mbar differential ± 4 iwc differential	0.1% RDG + 0.05% Span
EXT100m	0...100 mbar gauge 0...40 iwc	0.025% RDG + 0.025% FS
EXT400mC	± 400 mbar ± 160 iwc	0.025% RDG + 0.02% FS
EXT1C	± 1 bar -14.5...15 psi	0.025% RDG + 0.015% FS
EXT2C	-1...2 bar -14.5...30 psi	0.025% RDG + 0.01% FS
EXT6C	-1...6 bar -14.5...90 psi	0.025% RDG + 0.01% FS
EXT20C	-1...20 bar -14.5...300 psi	0.025% RDG + 0.01% FS
EXT60	0...60 bar 0...900 psi	0.025% RDG + 0.01% FS
EXT100	0...100 bar 0...1500 psi	0.025% RDG + 0.01% FS
EXT160	0...160 bar 0...2400 psi	0.025% RDG + 0.01% FS
EXT250	0...250 bar 0...3700 psi	0.025% RDG + 0.015% FS
EXT600	0...600 bar 0...9000 psi	0.025% RDG + 0.015% FS
EXT1000	0...1000 bar 0...15000 psi	0.025% RDG + 0.015% FS

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

2) The internal pressure module's range may also be displayed in absolute pressure if a barometric module is used.

3) The MC2 calibrator can hold one internal pressure module and the barometric option.

All external pressure modules (EXT) are also compatible with Beamex MC4, MC5, MC5P and MC6 calibrators.

Electrical generation, measurement and simulation

mV MEASUREMENT (T/C-TERMINALS) –25...150 mV

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
–25...150 mV	0.001 mV	0.02% RDG + 4 µV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	> 10 MΩ
Supported units	V, mV, µV
Display update rate	3 / second

mV GENERATION (T/C-TERMINALS) –25...150 mV

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
–25...150 mV	0.001 mV	0.02% RDG + 4 µV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Maximum load current	5 mA
Load effect	< 5 µV/mA
Supported units	V, mV, µV

58

VOLTAGE GENERATION –3...12 V

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
±0.25 V	0.01 mV	0.02% RDG + 0.1 mV
–3...–0.25 V	0.1 mV	0.02% RDG + 0.1 mV
0.25...12 V	0.1 mV	0.02% RDG + 0.1 mV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Maximum load current	5 mA
Load effect	< 50 µV/mA
Supported units	V, mV, µV

mA GENERATION (SOURCE/SINK) 0...25 mA

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0...25 mA	0.0001 mA	0.02% RDG + 1.5 µA

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Max load impedance (source)	750 Ω (0...20 mA), 600 Ω (20...25 mA)
Max loop voltage (sink)	60 V
Supported units	mA, µA

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

RESISTANCE MEASUREMENT 0...4000 Ω

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0...250 Ω	1 mΩ	4-wire connection: 0.02% RDG + 3.5 mΩ 3-wire connection: 0.02% RDG + 13.5 mΩ
250...2650 Ω	10 mΩ	
2650...4000 Ω	100 mΩ	

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Measurement current	Pulsed, bi-directional 1 mA (0..500 Ω), 0.2 mA (>500 Ω)
Supported units	Ω, kΩ
Display update rate	3 / second

RESISTANCE SIMULATION 0...4000 Ω

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0...400 Ω	10 mΩ	0.04% RDG or 30 mΩ (Whichever is greater)
400...4000 Ω	100 mΩ	0.04% RDG or 30 mΩ (Whichever is greater)

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Maximum resistance excitation current	5 mA (0...650 Ω) $I_{exc} \times R_{sim} < 3.25 \text{ V}$ (650...4000 Ω)
Settling time (pulsed currents)	1 ms
Supported units	Ω, kΩ

59

FREQUENCY GENERATION 0.0005...10 000 Hz

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0.0005...0.5 Hz	0.000001 Hz	0.01% RDG
0.5...5 Hz	0.00001 Hz	0.01% RDG
5...50 Hz	0.0001 Hz	0.01% RDG
50...500 Hz	0.001 Hz	0.01% RDG
500...5000 Hz	0.01 Hz	0.01% RDG
5000...10000 Hz	0.1 Hz	0.01% RDG

FEATURE	SPECIFICATION
Temperature coefficient	Specification valid from -10 to 50 °C (14...122°F)
Maximum load current	5 mA
Output amplitude positive square wave	0...12 Vpp ±(0.2 V+5%)
Output amplitude symmetric square wave	0...6 Vpp ±(0.2 V+5%)
Duty cycle	1...99% (0.0009...500 Hz), high / low time: min 25µs, max 1165 s
Supported units	Hz, kHz, cph, cpm, 1/Hz (s), 1/kHz (ms), 1/MHz (µs)
Jitter	< 0.28 µs

PULSE GENERATION 0...9 999 999 PULSES

FEATURE	SPECIFICATION
Range	0 to 9 999 999 pulses
Resolution	1 pulse
Maximum load current	5 mA
Output amplitude positive pulse	0...12 Vpp ±(0.2 V+5%)
Output amplitude symmetric pulse	0...6 Vpp ±(0.2 V+5%)
Pulse frequency	0.0005...10 000 Hz
Duty cycle	1...99% (0.0009...500 Hz), high / low time: min 25µs, max 1165 s

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

THERMOCOUPLE MEASUREMENT AND SIMULATION

Thermocouple types available as standard

TYPE	RANGE (°C)	RANGE (°C)	1 YEAR UNCERTAINTY (±) ⁽¹⁾
B ⁽²⁾	0...1820	0...200	⁽³⁾
		200...400	2.0 °C
		400...1820	1.0 °C
R ⁽²⁾	-50...1768	-50...0	1.0 °C
		0...100	0.8 °C
		100...1768	0.6 °C
S ⁽²⁾	-50...1768	-50...0	1.0 °C
		0...1768	0.7 °C
E ⁽²⁾	-270...1000	-270...-200 -200...1000	⁽³⁾ 0.25 °C
J ⁽²⁾	-210...1200	-210...1200	0.3 °C
K ⁽²⁾	-270...1372	-270...-200	⁽³⁾
		-200...1000	0.3 °C
		1000...1372	0.4 °C
N ⁽²⁾	-270...1300	-270...-200	⁽³⁾
		-200...1300	0.4 °C
T ⁽²⁾	-270...400	-270...-200	⁽³⁾
		-200...-100	0.3 °C
		-100...400	0.2 °C
U ⁽⁴⁾	-200...600	-200...-100	0.3 °C
		-100...600	0.2 °C
L ⁽⁴⁾	-200...900	-200...900	0.25 °C
C ⁽⁵⁾	0...2315	0...1000	0.4 °C
		1000...2000	0.8 °C
		2000...2315	1.2 °C
G ⁽⁶⁾	0...2315	0...100	⁽³⁾
		100...2315	1.0 °C
D ⁽⁵⁾	0...2315	0...1000	0.4 °C
		1000...2000	0.8 °C
		2000...2315	1.2 °C

FEATURE	MEASUREMENT	SIMULATION
Resolution	0.01 °C	0.01 °C
Temperature coefficient	< ±0.0015% of thermovoltage / °C outside of 18...28 °C < ±0.0008% of thermovoltage / °F outside of 64.4 ... 82.4°F	< ±0.0015% of thermovoltage / °C outside of 18...28 °C < ±0.0008% of thermovoltage / °F outside of 64.4 ... 82.4°F
Input impedance	>10 MΩ	–
Supported units	°C, °F, K	°C, °F, K
Display update rate	3 / second	–
Maximum load current	–	5 mA
Load effect	–	< 5 µV/mA

INTERNAL REFERENCE JUNCTION

RANGE (°C)	1 YEAR UNCERTAINTY
-10...50 °C	±0.25 °C

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

Uncertainty does not include reference junction uncertainty.

2) IEC 584, NIST MN 175, BS 4937, ANSI MC96.1

3) ±0.02% of thermovoltage + 4 µV

4) DIN 43710

5) ASTM E 988 - 96

6) ASTM E 1751 - 95e1

RTD MEASUREMENT AND SIMULATION

SENSOR TYPE	RANGE	RESOLUTION	MEASUREMENT 1 YEAR UNCERTAINTY (\pm) 1	SIMULATION 1 YEAR UNCERTAINTY (\pm) ^{1) 2)}
Pt 50 ... 1000	-200 ... 200°C	0.01°C	0.1°C	0.15°C
	200 ... 600°C	0.01°C	0.2°C	0.25°C
	600 ... 850°C	0.01°C	0.3°C	0.35°C
Ni 100	-60 ... 180°C	0.01°C	0.1°C	0.15°C
Ni 120	-80 ... 260°C	0.01°C	0.1°C	0.15°C
Cu10	-200 ... 260°C	0.01°C	0.2°C	0.8°C

FEATURE	MEASUREMENT	SIMULATION
Temperature coefficient	< $\pm 0.0015\%$ of resistance / °C outside of 18...28 °C < $\pm 0.0008\%$ of resistance / °F outside of 64.4 ... 82.4 °F	< $\pm 0.0015\%$ of thermovoltage / °C outside of 18...28 °C < $\pm 0.0008\%$ of thermovoltage / °F outside of 64.4 ... 82.4 °F
Maximum Resistance excitation current	–	5 mA (0 ... 650 Ω) $I_{exc} \times R_{sim} < 3.25$ V (650 ... 4000 Ω)
Supported units	°C, °F, K	°C, °F, K
Display update rate	3 / second	–

RTD TYPES AVAILABLE AS STANDARD				
Pt50 (385)	Pt400 (385)	Pt100 (3926)	Pt100 (3923)	Cu10 (427)
Pt100 (385)	Pt500 (385)	Pt100 (391)	Ni100 (618)	
Pt200 (385)	Pt1000 (385)	Pt100 (375)	Ni120 (672)	

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period. (k=2).

2) Specification valid with an excitation current >0.2 mA (0 ... 400 Ω), >0.1 mA (400 ... 4000 Ω)

STANDARD ACCESSORIES

- User guide
- Calibration certificate
- Internal rechargeable NiMH battery pack + battery charger
- Test leads and clips
- USB cable
- Adapter pressure connector – from G1/8" female to G 1/8" male with 60° internal cone (included in MC2-MF models)

OPTIONAL ACCESSORIES

- Pressure T-hose
- Soft carrying case
- Connection cable for external pressure modules
- Dry battery cartridge
- Calibration handpumps

Beamex MC2

A SERIES OF PRACTICAL HAND-HELD CALIBRATORS

62

The Beamex MC2-series includes three different high-quality hand-held calibrators for field use: the MC2 temperature/electrical calibrator and the MC2 multifunction calibrator. The MC2 is a compact and easy-to-use hand-held calibrator. It has a large graphical display, a menu-based interface and full numerical keyboard.

Compact and user-friendly

The MC2 is a compact, lightweight portable calibrator with large graphical display, multilingual interface and full numerical keyboard. Calibration is quick and simple.

Accuracy guaranteed

The calibrator is delivered with a traceable, accredited calibration certificate.

Safe and robust field calibrator

The MC2 with impact protectors and membrane keyboard is robust and made for tough use.

Wide range of configuration possibilities

The MC2 provides a number of configuration possibilities, such as internal and external pressure modules.



Main features

- ▶ Available in three versions:
 - MC2 temperature/electrical calibrator
 - MC2 multifunction calibrator
- ▶ Internal / external pressure modules
- ▶ Compact size and design
- ▶ User-friendly

Beamex MC5-IS

INTRINSICALLY SAFE MULTIFUNCTION CALIBRATOR



63

Made for extreme environments



Made for extreme environments



MC5-IS: designed for use in potentially explosive environments

The ATEX- and IECEx- certified MC5-IS is designed for use in potentially explosive environments, such as offshore platforms, oil refineries, chemical and petrochemical plants where inflammable gases may be present. There is probably no other intrinsically safe calibrator that can outperform the MC5-IS in terms of functionality. It is a documenting, multifunction calibrator that has calibration capabilities for pressure, temperature, electrical and frequency signals. Its modular design allows configuration based on your specific needs.



Main features of MC5-IS

Safe and robust field calibrator

The ATEX- and IECEx- certified, IP65-rated MC5-IS with impact protectors and membrane keyboard is robust and made for tough use.

Accuracy guaranteed

The MC5-IS is a highly accurate all-in-one calibrator. It is delivered with a traceable, accredited calibration certificate.

Communication with calibration software

Using the MC5-IS together with calibration software provides you with a complete documenting calibration system that produces calibration certificates automatically.

Unmatched functionality

No other intrinsically safe calibrator can outperform the MC5-IS in terms of functionality.



Additional features

Accuracy guaranteed

The MC5-IS is among the most accurate process calibrators available. As proof of this, each MC5-IS calibrator is delivered with a traceable, accredited calibration certificate.

Made for tough use

The IP65-rated robust casing, along with integrated impact protectors, makes the MC5-IS an ideal calibrator for use in wet and dusty environments subject to wide temperature variations.

Modularity means versatility

The MC5-IS is an extremely versatile calibrator with many different functions. The modular construction of the MC5-IS provides flexibility for the user. For instance, the MC5-IS can be ordered as a pressure or temperature stand-alone calibrator, and then later expand it into a data-logging, documenting multifunction calibrator.

66

Communication with calibration software

Using the MC5-IS together with calibration software provides you with a complete documenting calibration system that produces calibration certificates automatically. The benefits of the system include automated calibration procedures and paperless calibration management.

Calibrate safely

The MC5-IS is an intrinsically safe, ATEX- certified (Ex ia IIC T4 and ATEX directive II 1 G) multifunction calibrator. It is designed for use in potentially explosive environments, such as offshore platforms, oil refineries, chemical and petrochemical plants where inflammable gases may be present.

Fieldbus instruments must also be calibrated

Fieldbus installations are growing rapidly worldwide. Beamex is the first company in the world to answer to this demand. We have introduced the MC5-IS fieldbus calibrator, which provides capability for calibrating Foundation Fieldbus H1 or Profibus PA transmitters. It offers the safest possible way to calibrate fieldbus transmitters.

Specifications

GENERAL SPECIFICATIONS

GENERAL	
Display	96 x 72 mm (3.78" x 2.83"), 320 x 240 pixels, LCD
Weight	1.7 – 2.3 kg (3.7 – 5.1 lbs)
Dimensions	245 mm (9.6") x 192 mm (7.5") x 74 mm (2.9") (d/w/h)
Case protection	IP65 (dust and water proof)
Keyboard	Membrane protected individual keys
Battery type	Rechargeable NiMH, 1200 mAh, 8.4V DC
Battery operation	Average 5 hours
Charger supply	100...240 VAC, 50-60 Hz
Operating temperature	-10...50 °C (14...122°F)
Storage temperature	-20 to 60 °C (-4 to 140°F)
Humidity	0 to 80% R.H. non-condensing
Measurement sample rate	2.5 / second
Warranty	Standard: 3 years for MC5-IS; 1 year for battery pack. Warranty extension programs are also available.

FEATURES OF MODULES

67

FEATURE	INT	EXT	E	ET	RJ
Internal pressure modules	●				
External pressure modules		●			
Current measurement			●		
Voltage measurement			●		
Low voltage measurement			●		
Frequency measurement			●		
Pulse counting			●		
Switch sensing			●		
RTD measurement / simulation				●	
Resistance measurement / simulation				●	
TC measurement / simulation				●	
Low voltage measurement / generation				●	
Voltage generation				●	
Frequency generation				●	
Pulse generation				●	
Internal TC reference junction compensation					●

INT = Internal pressure module
 EXT = External pressure module
 E = Electrical measuring module
 ET = Electrical and temperature module
 RJ = Thermocouple reference junction module

INTERNAL & EXTERNAL PRESSURE MODULES

INTERNAL MODULES ¹⁾	EXTERNAL MODULES	RANGE ²⁾	RESOLUTION	ACCURACY ³⁾ (±)	1 YEAR UNCERTAINTY (±) ⁴⁾
INT B-IS	EXT B-IS	80 to 120 kPa a 800 to 1200 mbar a 11.6 to 17.4 psi a	0.01 0.1 0.001	0.03 kPa 0.3 mbar 0.0044 Psi	0.05 kPa 0.5 mbar 0.0073 psi
INT10mD-IS	EXT10mD-IS	±1 kPa diff ±10 mbar diff ±4 iwc diff	0.0001 0.001 0.001	0.05% Span	0.05% Span + 0.1% RDG
INT100m-IS	EXT100m-IS	0 to 10 kPa 0 to 100 mbar 0 to 40 iwc	0.0001 0.001 0.001	0.015% FS + 0.0125% RDG	0.025% FS + 0.025% RDG
INT400mC-IS	EXT400mC-IS	±40 kPa ±400 mbar ±160 iwc	0.001 0.01 0.001	0.01% FS + 0.0125% RDG	0.02% FS + 0.025% RDG
INT1C-IS	EXT1C-IS	±100 kPa ±1 bar -14.5 to 15 psi	0.001 0.00001 0.0001	0.007% FS + 0.0125% RDG	0.015% FS + 0.025% RDG
INT2C-IS	EXT2C-IS	-100 to 200 kPa -1 to 2 bar -14.5 to 30 psi	0.001 0.00001 0.0001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
INT6C-IS	EXT6C-IS	-100 to 600 kPa -1 to 6 bar -14.5 to 90 psi	0.01 0.0001 0.001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
INT20C-IS	EXT20C-IS	-100 to 2000 kPa -1 to 20 bar -14.5 to 300 psi	0.01 0.0001 0.001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
INT60-IS	EXT60-IS	0 to 6000 kPa 0 to 60 bar 0 to 900 psi	0.1 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
INT100-IS	EXT100-IS	0 to 10 MPa 0 to 100 bar 0 to 1500 psi	0.0001 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
INT160-IS	EXT160-IS	0 to 16 MPa 0 to 160 bar 0 to 2400 psi	0.0001 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
-	EXT250-IS	0 to 25 MPa 0 to 250 bar 0 to 3700 psi	0.001 0.01 0.1	0.007% FS + 0.0125% RDG	0.015% FS + 0.025% RDG
-	EXT600-IS	0 to 60 MPa 0 to 600 bar 0 to 9000 psi	0.001 0.01 0.1	0.007% FS + 0.01% RDG	0.015% FS + 0.025% RDG
-	EXT1000-IS	0 to 100 MPa 0 to 1000 bar 0 to 15000 psi	0.001 0.01 0.1	0.007% FS + 0.01% RDG	0.015% FS + 0.025% RDG

Temperature coefficient ±0.001% Rdg/ °C outside 15...35 °C (59...95 °F)

INT10mD-IS / EXT10mD-IS < ±0.002% Span/ °C outside 15...35 °C (59...95°F)

1) The MC5-IS calibrators can hold three internal pressure modules.

2) Every internal/external pressure module's range may also be displayed in absolute pressure if the barometric module (B) is installed.

3) 'Accuracy' includes hysteresis, nonlinearity, repeatability and reference standard uncertainty (k=2).

4) '1 Year Uncertainty' includes hysteresis, nonlinearity, repeatability and typical long-term stability for mentioned period (k=2).

All intrinsically safe external pressure modules (EXT-IS) are also compatible with Beamex MC2, MC2-IS, MC4, MC5, MC5P and MC6.

Supports the following pressure units as standard:

Pa, hPa, kPa, MPa, mbar, bar, lbf/ft², psi, gf/cm², kgf/cm², kp/cm², at, mmH₂O, cmH₂O, mH₂O, iwc, ftH₂O, mmHg, cmHg, mHg, inHg, mmHg(0 °C), inHg(0 °C), mmH₂O(4 °C), inH₂O(4 °C), ftH₂O(4 °C), inH₂O(60°F), mmH₂O(68°F), inH₂O(68°F), ftH₂O(68°F), torr, atm.

INT B-IS / EXT B-IS; M5 (10/32") female.

INT10mD-IS and EXT10mD-IS; Two M5 (10/32") female threads with a hose nipple included.

INT100m-IS/EXT100m-IS – INT20C-IS/EXT20C-IS; G1/8" (ISO228/1) female. A conical 1/8" BSP male with 60° internal cone adapter included for Beamex hose set.

INT60-IS, INT100-IS, INT160-IS; G1/8" (ISO228/1) female. EXT60-IS, EXT100-IS, EXT160-IS, EXT250-IS, EXT600-IS, EXT1000-IS; G ¼" (ISO228/1) male.

Wetted parts AISI316 stainless steel, Hastelloy, Nitrile rubber.

Maximum overpressure;

B module; 1200 mbar abs. 10mD module; 200 mbar. EXT600; 900 bar. EXT1000; 1000 bar.

For all other modules, the maximum overpressure is twice the nominal range.

HART is a registered trademark of HART Communication Foundation.

ELECTRICAL MODULE (E)

FUNCTION	RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
mV measurement ²	± 250 mV	0.001 mV	0.02% RDG + 5 μ V
V measurement ³	± 30 V	0.00001–0.001 V	0.02% RDG + 0.25 mV
mA measurement ⁴	± 100 mA	0.0001–0.001 mA	0.02% RDG + 1.5 μ A
Hz measurement ⁵	0.0028 to 50000 Hz	0.000001– 0.1 Hz	0.01% RDG
Pulse counting ⁵	0 to 9 999 999 pulses	1 pulse	N/A
mA Sink	0 to 25 mA	0.0001 mA	0.02% RDG + 1.5 μ A

Temperature coefficient < $\pm 0.001\%$ RDG / °C outside of 15...35 °C (59...95°F)

1) Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long-term stability for mentioned period (k=2).

2) Bias current < 10 nA

3) Impedance > 1 M Ω

4) Impedance < 7.5 Ω

5) MC5-IS; Impedance > 1 M Ω . Frequency measurement minimum amplitude 1 Vpp (< 10 kHz),

3 Vpp (10...50 kHz). Pulse counting minimum amplitude 1 Vpp (pulse length > 50 μ s),

3 Vpp (pulse length 50 μ s...10 μ s).

Trigger level range -1...+15 V.

TEMPERATURE ELECTRICAL MODULE (ET)

FUNCTION	RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
mV generation ⁽²⁾	± 250 mV	0.001 mV	0.02% RDG + 4 μ V
V generation ⁽³⁾	-2.5 to 10 V	0.00001–0.0001 V	0.02% RDG + 0.1 mV
mA sink	0 to 25 mA	0.0001 mA	0.02% RDG + 1 μ A
Hz generation ⁽⁴⁾	0.00028 to 50 000 Hz	0.000001 - 0.1 Hz	0.01% RDG
Pulse generation ⁽⁵⁾	0 to 9 999 999 pulses	1 pulse	N/A
Ohm simulation ⁽⁶⁾	1 to 4000 Ω	0.0–0.1 Ω	0.04% RDG or 30 m Ω ⁽⁷⁾
Ohm measurement ⁽⁸⁾	0 to 4000 Ω	0.001–0.1 Ω	0.02% RDG + 3.5 m Ω
mV measurement ⁽⁹⁾	± 250 mV	0.001 mV	0.02% RDG + 4 μ V

Temperature coefficient < $\pm 0.001\%$ RDG / °C outside of 15...35 °C (59...95°F)

1) Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long-term stability for mentioned period (k=2).

2) Load effect < 5 μ V/mA. Maximum output current 1 mA.

3) Load effect < 100 μ V/mA. Maximum output current 1 mA (0...10 V)

4) Amplitude range 0...5 Vpp (positive), 0...5 V (symmetric). Amplitude setting accuracy up to 5kHz \pm (200 mV + 5% of set value).

Waveforms: square wave (positive / symmetric) and sinewave (above 40 Hz).

5) Pulse generation frequency range 0.1...1000 Hz. Amplitude range 0...5 Vpp (positive), 0...5 V (symmetric).

6) Valid with measurement current 0.2...2 mA (1...250 Ω), 0.05 < I_{meas} • Rsim < 0.5 V (250...4000 Ω). Ω /RTD simulation settling time 1 ms.

7) Whichever is greater.

8) Specification valid with 4 wire connection. In 3 wire connection add 10 m Ω .

9) Bias current < 10 nA.

THERMOCOUPLE MEASUREMENT AND SIMULATION

TYPE	RANGE (°C)	RANGE (°C)	1 YEAR UNCERTAINTY (±) ⁽¹⁾
B ⁽²⁾	0...1820	0...200	⁽³⁾
		200...500	2.0 °C
		500...800	0.8 °C
		800...1820	0.6 °C
R ⁽²⁾	-50...1768	-50...0	1.0 °C
		0...150	0.7 °C
		150...1400	0.5 °C
		1400...1768	0.6 °C
S ⁽²⁾	-50...1768	-50...0	1.0 °C
		0...50	0.7 °C
		50...1500	0.6 °C
		1500...1768	0.7 °C
E ⁽²⁾	-270...1000	-270...-200	⁽³⁾
		-200...0	0.08% RDG + 0.07 °C
		0...600	0.015% RDG + 0.07 °C
		600...1000	0.026% RDG
J ⁽²⁾	-210...1200	-210...-200	⁽³⁾
		-200...0	0.07% RDG + 0.08 °C
		0...1200	0.02% RDG + 0.08 °C
K ⁽²⁾	-270...1372	-270...-200	⁽³⁾
		-200...0	0.1% RDG + 0.1 °C
		0...1000	0.02% RDG + 0.1 °C
		1000...1372	0.03% RDG
N ⁽²⁾	-270...1300	-270...-200	⁽³⁾
		-200...-100	0.2% RDG
		-100...0	0.05% RDG + 0.15 °C
		0...750	0.01% RDG + 0.15 °C
		750...1300	0.03% RDG
T ⁽²⁾	-270...400	-270...-250	⁽³⁾
		-250...-200	0.7 °C
		-200...0	0.1% RDG + 0.1 °C
		0...400	0.01% RDG + 0.1 °C
U ⁽⁴⁾	-200...600	-200...0	0.1% RDG + 0.15 °C
		0...600	0.01% RDG + 0.15 °C
L ⁽⁴⁾	-200...900	-200...0	0.07% RDG + 0.13 °C
		0...900	0.02% RDG + 0.13 °C
C ⁽⁵⁾	0...2315	0...900	0.4 °C
		900...2000	0.045% RDG
		2000...2315	1.2 °C
G ⁽⁶⁾	0...2315	0...70	⁽³⁾
		70...200	1.0 °C
		200...1600	0.5 °C
		1600...2000	0.7 °C
		2000...2315	1.0 °C
D ⁽⁵⁾	0...2315	0...1000	0.4 °C
		1000...2000	0.04% RDG
		2000...2315	1.2 °C

Resolution 0.01 °C.

With internal reference junction (module RJ) add 0.1 °C uncertainty.

Other thermocouple types also available as an option.

1) Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long-term stability for mentioned period (k=2).

2) IEC 584, NIST MN 175, BS 4937, ANSI MC96.1

3) ±(0.02% of thermovoltage + 4 µV)

4) DIN 43710

5) ASTM E 988 - 96

6) ASTM E 1751 - 95e1

REFERENCE JUNCTION MODULE (RJ)

RANGE (°C)	1 YEAR UNCERTAINTY (±) ⁽¹⁾
-10...50 °C	0.1 °C

1) Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long-term stability for mentioned period (k=2).

RTD MEASUREMENT AND SIMULATION

FUNCTION	RANGE (°C)	RANGE (°C)	MEASUREMENT 1 YEAR UNCERTAINTY (±) ¹⁾	SIMULATION 1 YEAR UNCERTAINTY (±) ¹⁾
Pt-sensors	-200 to 850 °C	-200 to 0 °C	0.06 °C	0.1 °C
		0 to 850 °C	0.025% RDG + 0.06 °C	0.025% RDG + 0.1 °C

1) Uncertainty includes reference standard uncertainty, hysteresis, nonlinearity, repeatability and typical long-term stability for mentioned period (k=2).

RTD TYPES AVAILABLE AS STANDARD				
Pt50 (385)	Pt400 (385)	Pt100 (3923)	Pt100 (3926)	Cu10 (427)
Pt100 (385)	Pt500 (385)	Pt100 (391)	Ni100 (618)	
Pt200 (385)	Pt1000 (385)	Pt100 (375)	Ni120 (672)	

To improve uncertainty with PRT (platinum RTD) sensors, the MC5-IS includes a standard possibility that allows you to create customized PRT sensors using the Callendar van Dusen correction coefficients. The easy-to-use Beamex PRT Tool PC software is used to create the sensor and to send it to the MC5-IS. Up to 100 customized PRT sensors can be stored in MC5-IS at one time.

This function may be also used to create new, non-supported PRT sensors in the MC5-IS. Both measurement and simulation can be done with the customized sensors.

STANDARD ACCESSORIES

- Accredited calibration certificate
- User guide
- Computer cable
- Battery charger / eliminator
- Internal NiMH battery pack
- Test leads and clips
- Appropriate pressure T-hose with internal low pressure modules
- CD-ROM with user manual, software tools and product information

OPTIONAL ACCESSORIES

- Soft carrying case
- Hard carrying case
- Spare battery pack

Beamex MC5-IS

INTRINSICALLY SAFE MULTIFUNCTION CALIBRATOR

The Beamex MC5-IS is ATEX- and IECEx- certified and designed for use in potentially explosive environments, such as offshore platforms, oil refineries, chemical and petrochemical plants where inflammable gases may be present. The MC5-IS is a documenting, multifunction calibrator that has calibration capabilities for pressure, temperature, electrical and frequency signals. Its modular design allows configuration based on your specific needs.

Safe and robust field calibrator

The ATEX- and IECEx- certified, IP65-rated MC5-IS with impact protectors and membrane keyboard is robust and made for tough use.

Accuracy assured

The MC5-IS is a highly accurate all-in-one calibrator. It is delivered with a traceable, accredited calibration certificate.

Communication with calibration software

Using the MC5-IS together with calibration software provides you with a complete documenting calibration system that produces calibration certificates automatically.

Unmatched functionality

No other intrinsically safe calibrator can outperform the MC5-IS in terms of functionality.



Main features

- ▶ Highly accurate all-in-one calibrator
- ▶ Designed for use in potentially explosive environments
- ▶ Calibration capabilities for pressure, temperature, electrical and frequency signals
- ▶ Certified in accordance with the ATEX directive and IECEx scheme
- ▶ HART Foundation Fieldbus H1 and Profibus PA support



Beamex MC2-IS

INTRINSICALLY SAFE MULTIFUNCTION CALIBRATOR



73

Practical tool for calibration in hazardous environments



A large, yellow industrial valve with a black handwheel is the central focus of the image. The valve is mounted on a yellow pipe with two red horizontal stripes. It is situated on a paved area with a brick pattern, surrounded by gravel. In the background, other yellow industrial equipment is visible, including pipes and valves, suggesting a hazardous environment like a refinery or chemical plant. The lighting is bright, and the overall scene is industrial and functional.

Practical tool for calibration in hazardous environments

The ATEX- and IECEx- certified MC2-IS is a compact calibrator for hazardous environments

The MC2-IS intrinsically safe multifunction calibrator is an ATEX- and IECEx- certified calibrator designed for use in potentially explosive environments such as offshore platforms, oil refineries, chemical and petrochemical plants where inflammable gases may be present. It connects to almost 20 available Beamex intrinsically safe external pressure modules. The calibrator has a compact size and design.



Main features of MC2-IS

Compact and user-friendly

The MC2-IS is a compact, lightweight, portable calibrator with a large graphical display, multilingual interface and full numerical keyboard. Calibration is quick and simple.

Accuracy guaranteed

The MC2-IS is delivered with a traceable, accredited calibration certificate.

Safe and robust field calibrator

The ATEX- and IECEx- certified MC2-IS with impact protectors and membrane keyboard is robust and made for tough use.

Extensive configuration possibilities

The MC2-IS provides a number of configuration possibilities and connects to nearly 20 available Beamex external pressure modules (IS).





The MC2-IS general specifications

GENERAL SPECIFICATIONS

GENERAL	MC2-IS
Display	60 mm x 60 mm (2.36" x 2.36"), 160 x 160 pixels LCD, backlit
Weight	1070 g (2.3 lbs)
Dimensions	215 mm (8.5") x 102 mm (4") x 49 mm (1.9") (d/w/h)
Keyboard	Membrane keyboard
Battery type	Rechargeable NiMH, 1700 mAh, 4.8V DC
Charging time	12 hours
Charger supply	100...240 VAC, 50–60 Hz
Battery operation	12 hours in measurement mode, backlight off. 4 hours when sourcing a loop, backlight continuously on.
Operating temperature	–10...50 °C (14...122°F)
Operating temperature when charging batteries	0...35 °C (32...95°F) (Must be charged at a non Ex area.)
Storage temperature	–20 to 60 °C (–4 to 140°F)
Humidity	0 to 80% R.H. non condensing
Warmup time	Specifications valid after a 5 minute warmup period.
Max. input voltage	30 V DC
Safety	Directive 73/23/EEC, EN 61010-1
EMC	Directive 89/336/EEC, EN 61326
Ex	IECEX: Ex ia IIC T4 Ga, Ta= –10 ...+50°C ATEX: Ex II 1 G, Ex ia IIC T4 Ga, Ta= –10 ...+50°C
Warranty	Standard: 2 years for MC2-IS; 1 year for battery pack. ⁽¹⁾

1) Warranty extension programs are also available.

77

VOLTAGE MEASUREMENT –1 ... 30 V DC

RANGE	RESOLUTION	1 YEAR UNCERTAINTY(±) ⁽¹⁾
±0.25 V	0.001mV	0.02% RDG + 5 µV
±(0.25...1 V)	0.01 mV	0.02% RDG + 5 µV
1...30 V	0.1 mV	0.02% RDG + 0.25 mV
–	1 mV	0.02% RDG + 0.25 mV

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	>1 MΩ
Supported units	V, mV, µV
Display update rate	3 / second

mA MEASUREMENT ±100 mA

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
±25mA	0.0001 mA	0.02% RDG + 1.5 µA
±(25...100 mA)	0.001 mA	0.02% RDG + 1.5 µA

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Input impedance	< 7.5 Ω
Supported units	mA, µA
Display update rate	3 / second

LOOP SUPPLY

FEATURE	SPECIFICATION
Maximum output current	> 25 mA, short circuit protected
Output voltage	20 V ± 10% @ 0 mA, > 12 V @ 20 mA
Output impedance in HART compatible mode	250 Ω ± 20%

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

Electrical measurements

FREQUENCY MEASUREMENT 0.0027...50 000 Hz

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
0.0027...0.5 Hz	0.000001 Hz	0.01% RDG
0.5...5 Hz	0.00001 Hz	0.01% RDG
5...50 Hz	0.0001 Hz	0.01% RDG
50...500 Hz	0.001 Hz	0.01% RDG
500...5000 Hz	0.01 Hz	0.01% RDG
5000...50000 Hz	0.1 Hz	0.01% RDG

FEATURE	SPECIFICATION
Temperature coefficient	Specification valid from -10 to 50 °C (14...122°F)
Input impedance	> 1 M Ω
Trigger level	-1...14 V in 1 V steps and open collector inputs
Minimum signal amplitude	2 Vpp (< 10 kHz), 3 Vpp (10...50 kHz)
Supported units	Hz, kHz, cph, cpm, 1/Hz (s), 1/kHz (ms), 1/MHz (μ s)
Gate period	267 ms + 1 signal period

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

78

PULSE COUNTING 0...9 999 999 PULSES

FEATURE	SPECIFICATION
Range	0 to 9 999 999 pulses
Input impedance	> 1 M Ω
Trigger level	-1...14 V in 1 V steps and open collector inputs
Minimum signal amplitude	2 Vpp (pulse length > 50 μ s), 3 Vpp (pulse length 10...50 μ s)

SWITCH TEST

FEATURE	SPECIFICATION	MC2-IS
Potential free contacts	Test voltage (trigger level)	3 V, 0.08 mA (1 V) or 20 V, 25 mA (2 V)
Voltage level detection	Trigger level Input impedance	-1...14 V in 1 V steps > 1 M Ω



Pressure measurement

INTERNAL PRESSURE MODULES (IPM)

INTERNAL MODULE ⁽³⁾	UNIT	RANGE ⁽²⁾	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
Barometric option -IS	Also enables absolute pressure measurement for the above pressure inputs. When using the barometric option, add 0.1 kPa (0.0146 psi) uncertainty for absolute pressure measurement.			

FEATURE	SPECIFICATION
Temperature coefficient	< $\pm 0.001\%$ RDG / °C outside 15...35 °C. < $\pm 0.0006\%$ RDG / °F outside 59...95°F
Maximum overpressure	2 \times Range
Pressure port	G 1/8" female with G 1/8" male (ISO 228/1) 60° internal cone adapter IPM160: G 1/8" female
Media compatibility	Wetted parts: AISI316 stainless steel, Nitrile rubber.
Supported pressure units	Pa, hPa, kPa, MPa, mbar, bar, lbf/ft ² , psi, ozf/in ² , gf/cm ² , kgf/m ² , kgf/m ² , kp/cm ² , at, mmH ₂ O, cmH ₂ O, mH ₂ O, iwc, ftH ₂ O, mmHg, cmHg, mHg, inHg, mmHg(0 °C), inHg(0 °C), mmH ₂ O(4 °C; 60 °F; 68 °F/20 °C), cmH ₂ O(4 °C; 60 °F; 68 °F/20 °C), inH ₂ O(4 °C; 60 °F; 68 °F/20 °C), ftH ₂ O(4 °C; 60 °F; 68 °F/20 °C), torr, atm, + four (4) user-configurable units
Display update rate	2.5 / second

EXTERNAL PRESSURE MODULES (EXT) STANDARD ACCURACY

INTRINSICALLY SAFE	RANGE ⁽²⁾	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
EXT200mC-s-IS	± 200 mbar	± 80 iwc 0.01 mbar 0.01 iwc	0.05% RDG + 0.05% FS
EXT2C-s-IS	-1...2 bar	-14.5...30 psi 0.0001 bar 0.001 psi	0.05% FS
EXT20C-s-IS	-1...20 bar	-14.5...300 psi 0.001 bar 0.01 psi	0.05% FS
EXT160-s-IS	0...160 bar	0...2400 psi 0.01 bar 0.1 psi	0.05% FS

EXTERNAL PRESSURE MODULES (EXT) HIGH ACCURACY

INTRINSICALLY SAFE	RANGE ⁽²⁾	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
Barometric-IS	800...1200 mbar abs	23.6...35.4 inHg a 0.5 mbar (0.015 inHg)
EXT10mD-IS	± 10 mbar differential	± 4 iwc differential 0.1% RDG + 0.05% Span
EXT100m-IS	0...100 mbar gauge	0...40 iwc 0.025% RDG + 0.025% FS
EXT400mC-IS	± 400 mbar	± 160 iwc 0.025% RDG + 0.02% FS
EXT1C-IS	± 1 bar	-14.5...15 psi 0.025% RDG + 0.015% FS
EXT2C-IS	-1...2 bar	-14.5...30 psi 0.025% RDG + 0.01% FS
EXT6C-IS	-1...6 bar	-14.5...90 psi 0.025% RDG + 0.01% FS
EXT20C-IS	-1...20 bar	-14.5...300 psi 0.025% RDG + 0.01% FS
EXT60-IS	0...60 bar	0...900 psi 0.025% RDG + 0.01% FS
EXT100-IS	0...100 bar	0...1500 psi 0.025% RDG + 0.01% FS
EXT160-IS	0...160 bar	0...2400 psi 0.025% RDG + 0.01% FS
EXT250-IS	0...250 bar	0...3700 psi 0.025% RDG + 0.015% FS
EXT600-IS	0...600 bar	0...9000 psi 0.025% RDG + 0.015% FS
EXT1000-IS	0...1000 bar	0...15000 psi 0.025% RDG + 0.015% FS

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

2) The pressure module's range may also be displayed in absolute pressure if a barometric module is used.

3) The MC2-IS does not have any internal pressure modules, but it does have a barometric option.

All external pressure modules (EXT-IS) are also compatible with Beamex MC2, MC4, MC5, MC6, MC5-IS and MC5P calibrators.

mV MEASUREMENT (T/C-TERMINALS) –25... 150 mV

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
–25... 150 mV	0.001 mV	0.02% RDG + 4 μ V

FEATURE	SPECIFICATION
Temperature coefficient	< $\pm 0.0015\%$ RDG / °C outside of 18...28 °C < $\pm 0.0008\%$ RDG / °F outside of 64.4...82.4°F
Input impedance	> 10 M Ω
Supported units	V, mV, μ V
Display update rate	3 / second

mV GENERATION (T/C-TERMINALS) –25... 150 mV

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
–25... 150 mV	0.001 mV	0.02% RDG + 4 μ V

FEATURE	SPECIFICATION
Temperature coefficient	< $\pm 0.0015\%$ RDG / °C outside of 18...28 °C < $\pm 0.0008\%$ RDG / °F outside of 64.4...82.4°F
Maximum load current	1 mA
Load effect	< 5 μ V/mA
Supported units	V, mV, μ V

VOLTAGE GENERATION –3... 11 V

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
± 0.25 V	0.01 mV	0.02% RDG + 0.1 mV
–3... –0.25 V	0.1 mV	0.02% RDG + 0.1 mV
0.25... 11 V	0.1 mV	0.02% RDG + 0.1 mV

FEATURE	SPECIFICATION
Temperature coefficient	< $\pm 0.0015\%$ RDG / °C outside of 18...28 °C < $\pm 0.0008\%$ RDG / °F outside of 64.4...82.4°F
Maximum load current	1 mA
Load effect	< 50 μ V/mA
Supported units	V, mV, μ V

mA GENERATION (SINK)

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (\pm) ⁽¹⁾
0... 25 mA	0.0001 mA	0.02% RDG + 1.5 μ A

FEATURE	SPECIFICATION MC2-IS
Temperature coefficient	< $\pm 0.0015\%$ RDG / °C outside of 18...28 °C < $\pm 0.0008\%$ RDG / °F outside of 64.4...82.4°F
Max load impedance (source)	none
Max loop voltage (sink)	30 V
Supported units	mA, μ A

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

RESISTANCE MEASUREMENT 0...4000 Ω

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0...250 Ω	1 mΩ	4-wire connection: 0.02% RDG + 3.5 mΩ
250...2650 Ω	10 mΩ	3-wire connection: 0.02% RDG + 13.5 mΩ
2650...4000 Ω	100 mΩ	

FEATURE	SPECIFICATION
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Measurement current	Pulsed, bi-directional 1 mA (0..500 Ω), 0.2 mA (>500 Ω)
Supported units	Ω, kΩ
Display update rate	3 / second

RESISTANCE SIMULATION 0...4000 Ω

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0...400 Ω	10 mΩ	0.04% RDG or 30 mΩ (whichever is greater)
400...4000 Ω	100 mΩ	0.04% RDG or 30 mΩ (whichever is greater)

FEATURE	SPECIFICATION MC2-IS
Temperature coefficient	< ±0.0015% RDG / °C outside of 18...28 °C < ±0.0008% RDG / °F outside of 64.4...82.4°F
Maximum resistance excitation current	4 mA (0...812 Ω) $I_{exc} \times R_{sim} < 3.25 \text{ V}$ (812...4000 Ω)
Settling time (pulsed currents)	1 ms
Supported units	Ω, kΩ

81

FREQUENCY GENERATION 0.0005...10 000 Hz

RANGE	RESOLUTION	1 YEAR UNCERTAINTY (±) ⁽¹⁾
0.0005...0.5 Hz	0.000001 Hz	0.01% RDG
0.5...5 Hz	0.00001 Hz	0.01% RDG
5...50 Hz	0.0001 Hz	0.01% RDG
50...500 Hz	0.001 Hz	0.01% RDG
500...5000 Hz	0.01 Hz	0.01% RDG
5000...10000 Hz	0.1 Hz	0.01% RDG

FEATURE	SPECIFICATION
Temperature coefficient	Specification valid from -10 to 50 °C (14...122°F)
Maximum load current	1 mA
Output amplitude positive square wave	0...11 Vpp ±(0.2 V+5%)
Output amplitude symmetric square wave	0...5.5 Vpp ±(0.2 V+5%)
Duty cycle	1...99% (0.0009...500 Hz), high / low time: min 25µs, max 1165 s
Supported units	Hz, kHz, cph, cpm, 1/Hz (s), 1/kHz (ms), 1/MHz (µs)
Jitter	< 0.28 µs

PULSE GENERATION 0...9 999 999 PULSES

FEATURE	SPECIFICATION
Range	0 to 9 999 999 pulses
Resolution	1 pulse
Maximum load current	1 mA
Output amplitude positive pulse	0...11 Vpp ±(0.2 V+5%)
Output amplitude symmetric pulse	0...5.5 Vpp ±(0.2 V+5%)
Pulse frequency	0.0005...10 000 Hz
Duty cycle	1...99% (0.0009...500 Hz), high / low time: min 25µs, max 1165 s

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

THERMOCOUPLE MEASUREMENT AND SIMULATION

Thermocouple types available as standard

TYPE	RANGE (°C)	RANGE (°C)	1 YEAR UNCERTAINTY (±) ⁽¹⁾
B ⁽²⁾	0...1820	0...200	⁽³⁾
		200...400	2.0 °C
		400...1820	1.0 °C
R ⁽²⁾	-50...1768	-50...0	1.0 °C
		0...100	0.8 °C
		100...1768	0.6 °C
S ⁽²⁾	-50...1768	-50...0	1.0 °C
		0...1768	0.7 °C
E ⁽²⁾	-270...1000	-270...-200 -200...1000	⁽³⁾ 0.25 °C
J ⁽²⁾	-210...1200	-210...1200	0.3 °C
K ⁽²⁾	-270...1372	-270...-200	⁽³⁾
		-200...1000	0.3 °C
		1000...1372	0.4 °C
N ⁽²⁾	-270...1300	-270...-200	⁽³⁾
		-200...1300	0.4 °C
T ⁽²⁾	-270...400	-270...-200	⁽³⁾
		-200...-100	0.3 °C
		-100...400	0.2 °C
U ⁽⁴⁾	-200...600	-200...-100	0.3 °C
		-100...600	0.2 °C
L ⁽⁴⁾	-200...900	-200...900	0.25 °C
C ⁽⁵⁾	0...2315	0...1000	0.4 °C
		1000...2000	0.8 °C
		2000...2315	1.2 °C
G ⁽⁶⁾	0...2315	0...100	⁽³⁾
		100...2315	1.0 °C
D ⁽⁵⁾	0...2315	0...1000	0.4 °C
		1000...2000	0.8 °C
		2000...2315	1.2 °C

FEATURE	MEASUREMENT	SIMULATION
Resolution	0.01 °C	0.01 °C
Temperature coefficient	< ±0.0015% of thermovoltage / °C outside of 18...28 °C < ±0.0008% of thermovoltage / °F outside of 64.4 ... 82.4°F	< ±0.0015% of thermovoltage / °C outside of 18...28 °C < ±0.0008% of thermovoltage / °F outside of 64.4 ... 82.4°F
Input impedance	>10 MΩ	–
Supported units	°C, °F, K	°C, °F, K
Display update rate	3 / second	–
Maximum load current	–	1 mA
Load effect	–	< 5 µV/mA

INTERNAL REFERENCE JUNCTION

RANGE (°C)	1 YEAR UNCERTAINTY
-10...50 °C	±0.25 °C

1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period (k=2).

Uncertainty does not include reference junction uncertainty.

2) IEC 584, NIST MN 175, BS 4937, ANSI MC96.1

3) ±0.02% of thermovoltage + 4 µV

4) DIN 43710

5) ASTM E 988 - 96

6) ASTM E 1751 - 95e1

RTD MEASUREMENT AND SIMULATION

SENSOR TYPE	RANGE	RESOLUTION	MEASUREMENT 1 YEAR UNCERTAINTY (\pm) 1	SIMULATION 1 YEAR UNCERTAINTY (\pm) ^{1) 2)}
Pt 50 ... 1000	-200 ... 200°C	0.01°C	0.1°C	0.15°C
	200 ... 600°C	0.01°C	0.2°C	0.25°C
	600 ... 850°C	0.01°C	0.3°C	0.35°C
Ni 100	-60 ... 180°C	0.01°C	0.1°C	0.15°C
Ni 120	-80 ... 260°C	0.01°C	0.1°C	0.15°C
Cu10	-200 ... 260°C	0.01°C	0.2°C	0.80°C

FEATURE	MEASUREMENT	SIMULATION
Temperature coefficient	< $\pm 0.0015\%$ of resistance / °C outside of 18...28 °C < $\pm 0.0008\%$ of resistance / °F outside of 64.4 ... 82.4 °F	< $\pm 0.0015\%$ of thermovoltage / °C outside of 18...28 °C < $\pm 0.0008\%$ of thermovoltage / °F outside of 64.4 ... 82.4 °F
Maximum Resistance excitation current	–	4 mA (0 ... 812 Ω) $I_{exc} \times R_{sim} < 3.25$ V (650 ... 4000 Ω)
Supported units	°C, °F, K	°C, °F, K
Display update rate	3 / second	–

RTD TYPES AVAILABLE AS STANDARD				
Pt50 (385)	Pt400 (385)	Pt100 (3926)	Pt100 (3923)	Cu10 (427)
Pt100 (385)	Pt500 (385)	Pt100 (391)	Ni100 (618)	
Pt200 (385)	Pt1000 (385)	Pt100 (375)	Ni120 (672)	

- 1) Uncertainty includes reference standard uncertainty, hysteresis, non-linearity, repeatability and typical long-term stability for the mentioned period. (k=2).
 2) Specification valid with an excitation current >0.2 mA (0 ... 400 Ω), >0.1 mA (400 ... 4000 Ω)

STANDARD ACCESSORIES

- User guide
- Calibration certificate
- Internal rechargeable NiMH battery pack + battery charger
- Test leads and clips
- USB cable

OPTIONAL ACCESSORIES

- Pressure T-hose
- Soft carrying case
- Connection cable for external pressure modules
- Calibration handpumps

Beamex MC2-IS

INTRINSICALLY SAFE MULTIFUNCTION CALIBRATOR

84

The MC2-IS intrinsically safe multifunction calibrator is an ATEX- and IECEx- certified calibrator designed for use in potentially explosive environments such as offshore platforms, oil refineries, chemical and petrochemical plants where inflammable gases may be present. It connects to almost 20 available Beamex intrinsically safe external pressure modules. The calibrator has a compact size and design.

Compact and user-friendly

The MC2-IS is a compact, lightweight, portable calibrator with a large graphical display, multilingual interface and full numerical keyboard. Calibration is quick and simple.

Accuracy guaranteed

The MC2-IS is delivered with a traceable, accredited calibration certificate.

Safe and robust field calibrator

The ATEX- and IECEx- certified MC2-IS with impact protectors and membrane keyboard is robust and made for tough use.

Extensive configuration possibilities

The MC2-IS provides a number of configuration possibilities and connects to nearly 20 available Beamex external pressure modules (IS).



Main features

- ▶ ATEX-certified intrinsically safe multifunction calibrator
- ▶ Connects to nearly 20 available Beamex intrinsically safe external pressure modules
- ▶ Compact size and design
- ▶ User-friendly



Beamex RTS24

TEMPERATURE SIMULATOR



7807734875883473388A3
E:886554@FBMS.com
7807734875883473388A3
E:886554@FBMS.com
7807734875883473388A3

High-precision instrument for the simulation of Pt-100 resistance thermometers

Beamex RTS24

The Beamex RTS24 is a high-precision instrument for the simulation of Pt-100 resistance thermometers. The RTS24 simulator covers the general operating range of Pt-100 thermometers with 24 calibration points. The simulator is small in size, rugged and easy to use and it has been especially designed for field use.


Technical specifications

TEMPERATURE VALUES IN °C (DIN 43760)					
-20	-10	-5	0	5	10
15	20	25	30	40	50
60	70	80	90	100	150
200	250	300	400	500	600

Accuracy	+/-0.05 % from indicated temperature value or +/-0.1 °C, whichever is larger. Stated accuracy is better than 1/2 DIN.
Temperature coefficient	+/- 0.001 %/°C, +/-0.0007 %/°F
Operating temperature	-20 °C to 70 °C, -4 °F to +155 °F
Dimensions	135 (h) x 104 (w) x 54 (d) mm, 5.3" (h) x 4.1" (w) x 2.1" (d)
Weight	350 g, 0.8 lb

86

APPLICATION



Beamex MB

METROLOGY TEMPERATURE BLOCK



Portable temperature dry block delivering bath-level accuracy for industrial applications

78077407588347338843
11796865405465486
7807402540254025132132131
552879558136458734657
888318757338848534900

Highly accurate temperature dry block

88



Portable temperature dry block delivering bath-level accuracy for industrial applications

The Beamex metrology temperature block (MB) is a user friendly and highly accurate temperature dry block. It delivers bath-level accuracy in a convenient dry block with temperature ranges from $-45\text{ }^{\circ}\text{C}$... $+700\text{ }^{\circ}\text{C}$. It enables you to take laboratory-level accuracy with you out into the field.

Main features of MB

High accuracy and stability

With a conventional dry block, you typically needed an external reference sensor if you wanted better accuracy. The Beamex MB has accurate internal temperature measurement and display accuracy up to $\pm 0.1\text{ }^{\circ}\text{C}$, so you can get high accuracy even without an external reference sensor. With the unique temperature control techniques the Beamex® MB has excellent stability up to $\pm 0.005\text{ }^{\circ}\text{C}$. This kind of stability has usually been found only in baths, not in dry blocks.

Built-in high-accuracy reference input

In order to receive the best accuracy from the MB, there is a possibility to connect an external reference sensor into the reference sensor connection (model). This eliminates the need for a separate reference thermometer. The reference sensor measurement is accurate up to $\pm 0.006\text{ }^{\circ}\text{C}$. ITS-90 or CV coefficients can be used to compensate any sensor errors.

Axial uniformity

With the unique dual zone control and extended well depth, the Beamex MB offers an excellent axial uniformity up to $\pm 0.02\text{ }^{\circ}\text{C}$.

Radial uniformity

Radial uniformity is the temperature difference between the holes in the block. It is naturally crucial that the reference sensor and the sensor being tested measure the same temperature. The Beamex MB offers radial uniformity up to $\pm 0.01\text{ }^{\circ}\text{C}$.

Immersion Depth

The Beamex MB series provides immersion depth up to 203 mm (160 mm for MB140), which, together with the control techniques, provides more stable calibration. Moreover, a deeper immersion depth reduces the stem conduction error (heat loss into the atmosphere), especially in higher temperatures.

Loading

With the extended well depth and the dual zone temperature control feature, the Beamex MB can correct the effect of loading and provides loading specifications up to $\pm 0.005\text{ }^{\circ}\text{C}$.



Beamex MB series specifications

	MB140	MB155	MB425	MB700
Temperature range at 23 °C	-45 °C to 140 °C (-49 °F to 284 °F)	-30 °C to 155 °C (-22 °F to 311 °F)	35 °C to 425 °C (95 °F to 797 °F)	50 °C to 700 °C ³⁾ (122 °F to 1292 °F)
Display accuracy	±0.1 °C Full range	±0.1 °C Full range	±0.1 °C to 100 °C ±0.15 °C to 225 °C ±0.2 °C to 425 °C	±0.2 °C to 425 °C ±0.25 °C to 660 °C
Stability	±0.005 °C Full range	±0.005 °C Full range	±0.005 °C to 100 °C ±0.008 °C to 225 °C ±0.01 °C to 425 °C	±0.005 °C to 100 °C ±0.01 °C to 425 °C ±0.03 °C to 700 °C
Axial uniformity 40 mm (1.6 in)	±0.08 °C to -35 °C ±0.04 °C to 0 °C ±0.02 °C to 50 °C ±0.07 °C to 140 °C	±0.025 °C to 0 °C ±0.02 °C to 50 °C ±0.05 °C to 155 °C	±0.05 °C to 100 °C ±0.09 °C to 225 °C ±0.17 °C to 425 °C	±0.09 °C to 100 °C ±0.22 °C to 425 °C ±0.35 °C to 700 °C
Radial uniformity	±0.01 °C Full range	±0.01 °C Full range	±0.01 °C to 100 °C ±0.02 °C to 225 °C ±0.025 °C to 425 °C	±0.01 °C to 100 °C ±0.025 °C to 425 °C ±0.04 °C to 700 °C
Loading effect (with a 6.35 mm reference probe and three 6.35 mm probes)	±0.02 °C to -35 °C ±0.005 °C to 100 °C ±0.01 °C to 140 °C	±0.005 °C to 0 °C ±0.005 °C to 100 °C ±0.01 °C to 155 °C	±0.01 °C Full range	±0.02 °C to 425 °C ±0.04 °C to 700 °C
Hysteresis	±0.025 °C	±0.025 °C	±0.04 °C	±0.07 °C
Immersion depth	160 mm (6.3 in)	203 mm (8 in)	203 mm (8 in)	203 mm (8 in)
Resolution	0.001 °C / °F			
Display	LCD, °C or °F, user-selectable			
Key pad	Ten key with decimal and +/- button. Function keys, menu key, and °C / °F key.			
Insert OD dimensions	30.0 mm (1.18 in)	30.0 mm (1.18 in)	30.0 mm (1.18 in)	29.2 mm (1.15 in)
Cooling time	44 min: 23 °C to -45 °C 19 min: 23 °C to -30 °C 19 min: 140 °C to 23 °C	30 min: 23 °C to -30 °C 25 min: 155 °C to 23 °C	220 min: 425 °C to 35 °C 100 min: 425 °C to 100 °C	235 min: 700 °C to 50 °C 153 min: 700 °C to 100 °C
Heating time	32 min: 23 °C to 140 °C 45 min: -45 °C to 140 °C	44 min: 23 °C to 155 °C 56 min: -30 °C to 155 °C	27 min: 35 °C to 425 °C	46 min: 50 °C to 700 °C
Size (H x W x D)	366 x 203 x 323 mm (14.4 x 8 x 12.7 in)			
Weight	14.2 kg (31.5 lb)	14.6 kg (32 lb)	12.2 kg (27 lb)	14.2 kg (31.5 lb)
Power requirements	230 VAC (±10%), 550 W 115 VAC (±10%), 550 W	230 VAC (±10%), 550 W 115 VAC (±10%), 550 W	230 VAC (±10%), 1025 W 115 VAC (±10%), 1025 W	230 VAC (±10%), 1025 W 115 VAC (±10%), 1025 W
Computer interface	RS-232			
Calibration	Accredited calibration certificate provided			
Environmental operating conditions	5 °C to 40 °C, 0% to 80% RH (non-condensing)			
Specifications valid in environmental conditions	18 °C...28 °C			

3) Calibrated to 660 °C; reference thermometer recommended at higher temperatures.

R MODEL SPECIFICATIONS	MB
Resistance range	0 Ω to 400 Ω
Resistance accuracy ¹⁾	0 Ω to 20 Ω: ±0.0005 Ω 20 Ω to 400 Ω: ±25 ppm of reading
Characterizations	ITS-90, CVD, Resistance
Temperature accuracy (100 ohm PRT) ²⁾	Below zero: ±(0.006 °C + 0.001% of temperature reading) Above zero: ±(0.006 °C + 0.003% of temperature reading)
Sensor connection	4-wire, 6-pin Lemo
Calibration	Accredited calibration certificate provided

1) Measurement accuracy specifications apply within the specified environmental operating conditions and assume 4-wires for PRTs.


2) The built-in reference thermometer readout accuracy does not include the sensor probe accuracy.

Inserts


INSERTS FOR MB MODELS

INSERT	MODEL	DESCRIPTION
MH1	All models	Multihole, metric / reference; ¼", 3 mm, 4 mm, 6 mm, 8 mm, 10 mm
MH2	All models	Multihole, metric / reference; ¼", 2x3 mm, 2x4 mm, 6 mm
B	All models	Blank
Special	All models	Special

Please contact Beamex for custom inserts.



MH1



MH2

STANDARD ACCESSORIES

- Power Cord
- RS-232 Cable
- User Guide
- Accredited Calibration Certificate
- LEMO Connector for reference sensor (R models only)
- Block Insulator (in MB140, MB155 and MB425)
- Tongs (insert removal tool)

OPTIONAL ACCESSORIES

- Transport Case for temperature block
- Inserts

Beamex MB

METROLOGY TEMPERATURE BLOCK

92

The Beamex metrology temperature block (MB) is a highly accurate temperature dry block. It delivers bath-level accuracy in a convenient dry block. It enables you to take laboratory level accuracy with you out into the field. The unique dual zone control technology enables excellent stability and uniformity. Immersion depth up to 203 mm and temperature ranges from -45 °C ... $+700\text{ °C}$.

Compact and user-friendly

The MB is a compact, lightweight, portable calibrator with a large graphical display, multilingual interface and full numerical keyboard. Calibration is quick and simple.

Accuracy guaranteed

- MB140 / MB140R with range -45 °C ... $+140\text{ °C}$
- MB155 / MB155R with range -30 °C ... $+155\text{ °C}$
- MB425 / MB425R with range $+35\text{ °C}$... $+425\text{ °C}$
- MB700 / MB700R with range $+50\text{ °C}$... $+700\text{ °C}$

The R models include an internal reference thermometer with a connection for an external reference sensor.

Smart reference probes

Beamex smart reference probes are high-quality and extremely stable reference PRT probes with an integrated memory to store the individual probe coefficients. They are available in two versions: 300 mm straight version or a 90° bent version.



Main features

- ▶ High accuracy – a dry block that delivers bath-level accuracy
- ▶ The unique dual zone control technology enables excellent stability and uniformity
- ▶ Immersion depth up to 203 mm
- ▶ Wide temperature range from -45 °C to $+700\text{ °C}$
- ▶ Accredited calibration as standard
- ▶ Part of the Beamex ICS integrated calibration solution

Beamex FB

FIELD TEMPERATURE BLOCK



Lightweight, highly accurate temperature dry block for industrial field use

7307734873080347308043
11790865407465486
7307734873080347308043
525979558136458734657
50534875730818534900

An ideal temperature block for industrial field use



Lightweight, highly accurate temperature dry block for industrial field use

The Beamex field temperature block (FB) is an ideal temperature block for industrial field use. It is lightweight and easy to carry. It is an extremely quick dry block, yet it provides excellent accuracy.

Main features of the Beamex FB

Lightweight, portable

The Beamex FB field temperature block is ideal for industrial field use. It only weighs about 8 kg, and it is small enough to carry around.

Speed

The Beamex FB is extremely quick to reach various temperatures, i.e. it cools down to $-25\text{ }^{\circ}\text{C}$ in 15 minutes and heats up to $+660\text{ }^{\circ}\text{C}$ in 15 minutes. This saves time and increases productivity.

Accuracy and performance

The Beamex FB is an easily portable unit that also provides excellent calibration accuracy. The display accuracy is up to $\pm 0.2\text{ }^{\circ}\text{C}$ and its control technology provides great stability up to $\pm 0.01\text{ }^{\circ}\text{C}$. The dual zone controlled block provides excellent axial uniformity up to $\pm 0.04\text{ }^{\circ}\text{C}$ and radial uniformity up to $\pm 0.01\text{ }^{\circ}\text{C}$.

Smart reference sensors

The Beamex FB has an internal reference thermometer (in R models), which enables connections to the Beamex smart reference sensors. These sensors have a memory that contains all of the sensor correction data. This enables the use of the reference sensor as a real plug-and-play.

Accredited calibration

Each Beamex FB field temperature block is delivered with an accredited calibration certificate.

Usability

The large LCD display, function keys and multilingual, menu-based user interface makes the Beamex FB easy to use. A graphic and audible stability indicator lets you know when a block is stable. The HOT warning light indicates when the block is hot (over $+50\text{ }^{\circ}\text{C}$). It blinks as long as the block is too hot to touch, even when the unit is switched off or when the mains cable is disconnected.

Part of the Beamex ICS integrated calibration solution

The communication port enables communication with selected Beamex MC calibrators for automation calibration and documentation, making the Beamex FB products part of the Beamex ICS integrated calibration solution. Combined with the Beamex MC6 calibrator, loop calibrations are possible with conventional, HART and Fieldbus temperature transmitters with sensors.



Beamex FB series specifications

	FB150	FB350	FB660
Temperature range at 23 °C	-25 °C to 150 °C (-13 °F to 302 °F)	33 °C to 350 °C (91 °F to 662 °F)	50 °C to 660 °C (122 °F to 1220 °F)
Display accuracy	±0.2 °C Full range	±0.2 °C Full range	±0.35 °C at 50 °C ±0.35 °C at 420 °C ±0.5 °C at 660 °C
Stability	±0.01 °C Full range	±0.02 °C at 33 °C ±0.02 °C at 200 °C ±0.03 °C at 350 °C	±0.03 °C at 50 °C ±0.05 °C at 420 °C ±0.05 °C at 660 °C
Axial uniformity at 40 mm (1.6 in)	±0.05 °C Full range	±0.04 °C at 33 °C ±0.1 °C at 200 °C ±0.2 °C at 350 °C	±0.05 °C at 50 °C ±0.35 °C at 420 °C ±0.5 °C at 660 °C
Radial uniformity	±0.01 °C Full range	±0.01 °C at 33 °C ±0.015 °C at 200 °C ±0.02 °C at 350 °C	±0.02 °C at 50 °C ±0.05 °C at 420 °C ±0.10 °C at 660 °C
Loading effect (with a 6.35 mm reference probe and three 6.35 mm probes)	±0.006 °C Full range	±0.015 °C Full range	±0.015 °C at 50 °C ±0.025 °C at 420 °C ±0.035 °C at 660 °C
Hysteresis	±0.025 °C	±0.03 °C	±0.01 °C
Immersion depth	150 mm (5.9 in)		
Insert OD dimensions	30 mm (1.18 in)	25.3 mm (0.996 in)	24.4 mm (0.96 in)
Heating time	16 min: 23 °C to 140 °C 23 min: 23 °C to 150 °C 25 min: -25 °C to 150 °C	5 min: 33 °C to 350 °C	15 min: 50 °C to 660 °C
Cooling time	15 min: 23 °C to -25 °C 25 min: 150 °C to -25 °C	32 min: 350 °C to 33 °C 14 min: 350 °C to 100 °C	35 min: 660 °C to 50 °C 25 min: 660 °C to 100 °C
Resolution	0.01 °C / °F		
Display	LCD, °C or °F user-selectable		
Size (H x W x D)	290 mm x 185 mm x 295 mm (11.4 x 7.3 x 11.6 in)		
Weight	8.16 kg (18 lb)	7.3 kg (16 lb)	7.7 kg (17 lb)
Power requirements	230 V (±10%) 50/60 Hz, 575 W 100 V to 115 V (±10%) 50/60 Hz, 635 W	230 V (±10%), 50/60 Hz, 1800 W 100 V to 115 V (±10%), 50/60 Hz, 1400 W	230 V (±10%), 50/60 Hz, 1800 W 100 V to 115 V (±10%), 50/60 Hz, 1400 W
Computer interface	RS-232	RS-232	RS-232
Calibration	Accredited calibration certificate provided		
Environmental operating conditions	0 °C to 50 °C, 0% to 90% RH (non-condensing)		
Specifications valid in environmental conditions	13 °C...33 °C		

R MODEL SPECIFICATIONS	FB
Resistance range	0 Ω to 400 Ω
Resistance accuracy ¹⁾	0 Ω to 42 Ω: ±0.0025 Ω 42 Ω to 400 Ω: ±60 ppm of reading
Characterizations	ITS-90, CVD, IEC-60751, resistance
Temperature accuracy (100 ohm PRT) ²⁾	±(0.015 °C + 0.008% of temperature reading)
Sensor connection	4-wire, 6-pin Smart Lemo
Calibration	Accredited calibration certificate provided

1) Measurement accuracy specifications apply within the specified environmental operating conditions and assume 4-wires for PRTs.


2) The built-in reference thermometer readout accuracy does not include the sensor probe accuracy.

Inserts


INSERTS FOR FB MODELS

INSERT	MODEL	DESCRIPTION
MH1	FB150	Multihole, metric / reference; ¼", 3 mm, 4 mm, 6 mm, 8 mm, 10 mm
MH1	FB350, FB660	Multihole, metric / reference; ¼", 4 mm, 6 mm, 8 mm, 10 mm
MH2	All models	Multihole, metric / reference; ¼", 2x3 mm, 2x4 mm, 6 mm
B	All models	Blank
Special	All models	Special


Please contact Beamex for custom inserts.




FB150-MH1



FB150-MH2



FB350-MH1, FB660-MH1



FB350-MH2, FB660-MH2

STANDARD ACCESSORIES

- Power Cord
- RS-232 Cable
- User Guide
- Accredited Calibration Certificate
- LEMO Connector for reference sensor (R models only)
- Block Insulator (in FB150)
- Tongs (insert removal tool)

OPTIONAL ACCESSORIES

- Transport Case for temperature block
- Inserts

Beamex FB

FIELD TEMPERATURE BLOCK

98

Lightweight, highly accurate temperature dry block for industrial field use. The Beamex field temperature block (FB) is an ideal temperature block for industrial field use. It is lightweight and easy to carry. It is an extremely quick dry block, yet it provides excellent accuracy.

Available models

- FB150 / FB150R with range $-25\text{ °C} \dots +150\text{ °C}$
- FB350 / FB350R with range $+33\text{ °C} \dots +350\text{ °C}$
- FB660 / FB660R with range $+50\text{ °C} \dots +660\text{ °C}$

The R models include an internal reference thermometer with a connection for an external reference sensor.

Smart reference probes

Beamex smart reference probes are high-quality extremely stable reference PRT probes with an integrated memory which stores the individual probe coefficients. They are available in two versions: 300 mm straight version or a 90° bent version.



Main features

- ▶ Lightweight, portable and quick field block
- ▶ Highly accurate
- ▶ Temperature ranges from a -25 °C to $+660\text{ °C}$
- ▶ Dual zone control techniques enable excellent stability and uniformity
- ▶ Accredited calibration certificate as standard
- ▶ Part of the Beamex ICS integrated calibration solution

BEAMEX SMART REFERENCE PROBES



Smart reference probes

The Beamex smart reference probe is a high-quality and extremely stable PRT probe with an integrated memory that stores the individual sensor coefficients. The sensor works as plug-and-play with Beamex FB series of temperature blocks (R model). The temperature block automatically reads the sensor coefficients from the sensor and makes the necessary adjustments. This

eliminates the need to enter the coefficients manually. The sensor can also be used with the Beamex MB series of temperature blocks (R model). The sensor coefficients can be manually entered via the MB user interface. The sensor is available as a 300 mm straight version or a 90° bent version, making it an ideal reference sensor for the Beamex temperature block.

MAIN FEATURES:

- Temperature range -200 °C... 420 °C / 660 °Ct
- High stability, up to ± 0.007 °C
- 300 mm straight and 90° bent versions
- Accredited calibration certificate with data and ITS-90 coefficients included as standard



MODEL	DESCRIPTION
RPRT-420-300	Reference PRT, max 420 °C, length 300 mm, straight
RPRT-420-230A	Reference PRT, max 420 °C, length 230 mm (before angle), 90° angled
RPRT-660-300	Reference PRT, max 660 °C, length 300 mm, straight
RPRT-660-230A	Reference PRT, max 660 °C, length 230 mm (before angle), 90° angled

SPECIFICATIONS

PARAMETER	RPRT-420-300 & RPRT-420-230A	RPRT-660-300 & RPRT-660-230A
Temperature range	-200 to 420 °C	- 200 to 660 °C
Nominal resistance at 0.010 °C	100 Ω ±0.5 Ω	100 Ω ±0.5 Ω
Temperature coefficient	0.003925 Ω/Ω/°C	0.0039250 Ω/Ω/°C
Sheath diameter x length	Straight: 6.35 mm ±0.08 mm x 305mm ±3 mm (0.25 in ±0.003 x 12 in ±0.13 in) Angled: 6.35 mm ±0.08 mm x 300 mm ±6 mm (0.25 in ±0.003 x 11.75 in ±0.25 in)	6.35 mm ±0.08 mm x 305 mm ±0.08 mm (0.25 in ±0.003 x 12 in ±0.13 in)
Short-term repeatability ¹⁾	±0.007 °C at 0.010 °C ±0.013 °C at max temp	±0.007 °C at 0.010 °C ±0.013 °C at max temp
Drift ²⁾	±0.007 °C at 0.010 °C ±0.013 °C at max temp	±0.007 °C at 0.010 °C ±0.013 °C at max temp
Hysteresis	±0.010 °C maximum	±0.010 °C maximum
Sensor length	50.8 mm (2.0 in)	30 mm ±5 mm (1.2 in ±0.2 in)
Sensor location	9.5 mm ±3.2 mm from tip (0.375 in ±0.13 in)	3 mm ±1 mm from tip (0.1 in ±0.1 in)
Sheath material	Inconel 600	Inconel 600
Maximum immersion (nominal)	Straight: 305 mm (12 in) Angled: 210 mm (8.3 in)	Straight: 305 mm (12 in) Angled: 210 mm (8.3 in)
Minimum immersion (<5 mK error)	102 mm (4.0 in)	100 mm (3.9 in)
Minimum insulation resistance	500 MΩ at 23 °C	500 MΩ at 23 °C, 10 MΩ at 670 °C
Transition junction temperature range ³⁾	-50 °C to 150 °C	-50 °C to 200 °C
Transition junction dimensions	Straight: 76.2 mm x 10.7 mm (3.0 in x .38 in) Angled: 70 mm x 10.6 mm (2.8 in x .42 in)	71 mm x 12.5 mm (2.8 in x .42 in)
Typical response time	8 seconds	12 seconds
Self heating (in 0 °C bath)	60 mW/°C	50 mW/°C
Lead-wire cable	Teflon cable, Teflon insulated, 24 AWG stranded, silverplated copper	Teflon cable, Teflon insulated, 24 AWG stranded, silver plated copper
Lead-wire length	1.8 m (6 ft)	1.8 m (6 ft)
Lead-wire temperature range	-50 °C to 150 °C	-50 °C to 250 °C

1) Three thermal cycles from min to max temp, includes hysteresis, 95% confidence

2) After 100 hrs at max temp, 95% confidence

3) Temperatures outside this range will cause irreparable damage. For best performance, transition junction should not be too hot to touch.



Beamex POC6

AUTOMATIC PRESSURE CONTROLLER



780773487588347338843
11790865405465486
780740254025402132132131
52587955838458734657
88534875733878534900

Pressure calibration made fast and easy

An accurate and user-friendly automatic pressure output controller

The Beamex POC6 is an accurate and user-friendly automatic pressure output controller, providing regulated output from vacuum to 100 bar (1450 psi). The POC6 can be delivered as a panel mounted to the Beamex MCS200 modular test and calibration system or as a portable desk top version.

The POC6 can be used as a stand-alone pressure controller or it can be integrated into the Beamex calibration system. Together with the MC6 and Beamex CMX calibration software, the POC6 offers a fully automated, integrated solution for performing, documenting and managing calibrations easily, efficiently and accurately.

102

Main features of the POC6

User friendly

With its touch screen, the POC6 is fast and efficient to use.

Panel mounted to a Beamex workstation

The POC6 can be used as panel mounted to a Beamex MCS200 modular test and calibration system.

Portable desk top version

The POC6 can also be used as a desk top pressure controller, which makes it a very mobile solution.

Part of Beamex ICS integrated calibration solution

Together with the Beamex MC6 or MC5P calibrators as well as the Beamex CMX calibration software, the POC6 offers an integrated, automated calibration system for performing, documenting and managing calibrations easily and efficiently.



General specifications

FEATURE	SPECIFICATION
Display	7.0" color LCD with touch screen
Weight	Approx. 9.1 kg (20 lbs)
Dimensions	Portable: 228(w) x 148(h) x 310(d) mm (without handle) Panel mounting: – Workstation, mobile trolley: 321(w) x 200(h) mm – Desktop cabinet: 321(w) x 178(h) mm
Digital interface	RS232, Ethernet, IEEE-488
Power consumption	Max. 90 VA
Warranty	2 years
Supported user interface languages	English, German, French, Spanish, Italian, Chinese, Russian, Japanese, Polish, Portuguese, Korean
Communication emulation	DPI510
Connections	Pressure supply, Vacuum supply, Test port All connections 7/16"-20 SAE

SPECIFICATIONS

FEATURE	SPECIFICATION
Output range	± 1 bar (±14.5 psi) –1 to 6 bar (–14.5 to 87 psi) –1 to 20 bar (–14.5 to 290 psi) –1 to 70 bar (–14.5 to 1,015 psi) –1 to 100 bar (–14.5 to 1450 psi) Special range within –1 to 100 bar (–14.5 to 1450 psi)
Precision	< 0.015 % FS
1 year uncertainty	< 0.025 % FS
Pressure units	33 selectable and 2 programmable
Control stability	< 0.004 % FS
Slew rate	< 3 sec. (regarding a 10 % press. increase in a 250 ml test volume)
Control range maximum	From 0 up to 100 % FS
Test volume	50 to 1,000 ccm (without throttle)
Pressure media	Clean dry non-corrosive gases
Overpressure protection	Safety relief valve
Resolution	4 to 6 digits
Measuring rate	25/sec
Max overpressure	Supply port 110 % FS Test port max. 105 % FS
Supply pressure range	Minimum 100%, Maximum 110% of nominal pressure range
Compensated temperature range	15 to 45 °C
Operation temperature	0... 50°C

INSTALLATION ALTERNATIVES

- Portable unit
- Panel mounted to a workstation
 - desktop cabinet
 - mobile trolley

STANDARD ACCESSORIES

- User guide
- Accredited calibration certificate
- Mains cable
- Connecting kits for:
 - High pressure and vacuum supply or
 - Low pressure and vacuum supply with appropriate pressure adapters and hoses

OPTIONS

- Barometric precision reference
 - enables absolute range
- Panel mounting kit
- Bezel and handle
- Carrying case

Beamex POC6

AUTOMATIC PRESSURE CONTROLLER

104

The Beamex POC6 is an accurate and user-friendly automatic pressure output controller, providing regulated output from vacuum to 100 bar (1450 psi). The POC6 can be delivered as a panel mounted to Beamex workstations or as a portable desk top version. The POC6 can be used as a stand-alone pressure controller or it can be integrated into the Beamex calibration system. Together with the MC6 and Beamex CMX calibration software, the POC6 offers a fully automated, integrated solution for performing, documenting and managing calibrations easily, efficiently and accurately.

User friendly

With its touch screen, the POC6 is fast and efficient to use.

Panel mounted to a Beamex workstation

The POC6 can be delivered and used as panel mounted to a Beamex MCS200 workstation.

Portable desk top version

The POC6 can also be used as a desk top pressure controller, which makes it a very mobile solution.

Part of Beamex ICS integrated calibration solution

Together with the Beamex MC6 or MC5P calibrator as well as the Beamex CMX calibration software, the POC6 offers an integrated, automated calibration system for performing, documenting and managing calibrations easily and efficiently.



Main features

- ▶ User-friendly
- ▶ Part of the Beamex ICS integrated calibration solution
- ▶ Can be used as a stand-alone pressure controller
- ▶ Automatic pressure calibrations
- ▶ Portable or bench mounted

Beamex PG

PRESSURE GENERATORS

780773487388347338843
780773487388347338843
780773487388347338843
780773487388347338843
780773487388347338843



Beamex **PGXH | PGPH | PGM | PGL | PGV**

Beamex PG pressure generators are portable hand-operated pressure generators and ultimate field calibration pumps


Calibration pumps

106



PGXH

PRESSURE GENERATOR EXTRA HIGH 0 ... 700 bar / 0 ... 10 000 psi




The PGXH is a hand-operated, hydraulic, high-pressure generator compatible with many different liquids (e.g. mineral oil, distilled water, etc.). The pump is equipped with an adjustable volume control for fine-tuning generated pressure. The PGXH can be equipped with an optional relief valve providing adjustable over pressure protection in different ranges.

PGPH

PRESSURE GENERATOR PNEUMATIC HIGH –0.95 ... 140 bar / –13.7 ... 2 000 psi


108



The PGPH is a hand-operated pneumatic (air as pressure medium) high-pressure table pressure generator. The pump is efficient in generating both vacuum and high pressure up to 140 bar (2,000 psi) quickly and effortlessly. It takes less than one minute to generate the maximum pressure. The PGPH is equipped with an adjustable volume control, providing excellent fine-tuning of generated pressure, and two hand-tight connectors allowing fast and easy connections without the need for any tools.

PGM

PRESSURE GENERATOR MEDIUM 0 ... 20 bar / 0 ... 300 psi



The PGM is a hand-operated pressure calibration pump that uses air as its pressure medium. The extremely accurate volume control provides the excellent fine adjustment of pressure. The pump's unique and sturdy construction makes the PGM the ultimate field calibration pump.

PGL

PRESSURE GENERATOR LOW –400 ... 400 mbar / –160 ... 160 iwc



110

The PGL is a hand-operated pressure table pump for low pressure using air as its pressure medium. The pump is equipped with an isothermal bellows chamber for reducing possible environmental temperature changes during the calibration process. With the screw-operated volume control and fine adjustment, an extremely accurate and stable pressure adjustment is possible.

PGV

VACUUM GENERATOR 0 ... -0.95 bar / 0 ... -13.7 psi



The PGV is a highly efficient vacuum pump generating vacuum quickly using a pulling action. The extensive volume control provides fine adjustment of the generated vacuum. The compact, sturdy and lightweight construction is designed for use in tough field environments.

Specifications

PGXH, PRESSURE GENERATOR EXTRA HIGH	
Output pressure:	0...700 bar / 0...10 000 psi
Pressure media:	Mineral oil, distilled water
Outlet threads:	G 3/8" female (ISO228/1) G 1/4" female (with adaptor)
Dimensions:	236 mm x 159 mm x 70 mm 9.29" x 6.26" x 2.76"
Weight:	1.6 kg / 3.53 lb
Standard delivery:	<ul style="list-style-type: none"> Carrying case High pressure hose with 1/4" NPT and G 1/4" male connectors
Optional accessories:	Relief valve

PGM, PRESSURE GENERATOR MEDIUM	
Output pressure:	0...20 bar / 0...300 psi
Pressure media:	Air
Outlet connector:	2 x 1/8" NPT female
Dimensions:	223 mm x 96 mm x 38 mm 8.78" x 3.78" x 1.5"
Weight:	400 g / 0.9 lb
Standard delivery:	<ul style="list-style-type: none"> Service seal kit Opening tool Output adapters: <ul style="list-style-type: none"> G 1/8" male 60° int. cone 2 x connector for 1/8" ID hose 2 x connector for 1/8" ID / 1/4" OD hose with nut - plug
Optional accessories:	<ul style="list-style-type: none"> Carrying case Hose 1.5 m T-tubing set with connectors

PGV, PRESSURE GENERATOR VACUUM	
Output pressure:	0...-0.95 bar / 0...-13.7 psi
Pressure media:	Air
Outlet connector:	G 1/8" male 60° int. cone
Dimensions:	Diameter 35 mm / 1.38" Length, min 230 mm / 9.06" Length, max 322 mm / 12.68"
Weight:	340 g / 0.75 lb
Standard delivery:	<ul style="list-style-type: none"> Service seal kit Opening tool R 1/8" 60° female to 1/4 NPT male for connecting the pressure measurement hose to the instrument to be calibrated. Pressure hose 0.75 m / 2'5 1/2" with R 1/8" 60° male connector at both ends
Optional accessories:	<ul style="list-style-type: none"> Carrying case T-tubing set with connectors 1.5 m / 4'9 hose

PGPH, PRESSURE GENERATOR PNEUMATIC HIGH	
Pressure range:	-0.95...140 bar / -13.7...2 000 psi
Output threads:	2 x G 1/4" female
Temperature:	0...50 °C / 32...122 °F
Humidity:	< 85% RH
Adjusting fineness:	0.1 mbar (0.001 psi)
Safety pressure:	< 180 bar (2 600 psi)
Pressure media:	Air
Dimensions:	54 cm x 27 cm x 18 cm 21.26" x 10.63" x 7.09"
Weight:	7.1 kg / 15.7 lb
Standard delivery:	<ul style="list-style-type: none"> Output connectors: <ul style="list-style-type: none"> G 1/4" (Male) Plug x 1 A small bag (20 pcs.) of o-rings (sealing rings) type: NBR70 (size 6x2) User guide
Optional accessories:	<ul style="list-style-type: none"> Carrying case Maintenance kit Lubricant for the axle of fine adjustment High pressure hose 1 m with G 1/4" and G 1/8" male connectors for connecting the pump to the calibrator's internal high pressure module (not needed if an external high pressure module is available) High pressure hose 1 m with G 1/4" and 1/4" NPT connectors for connecting the pump to the instrument

PGL, PRESSURE GENERATOR LOW	
Pressure range:	-400...400 mbar / -160...160 iwc
Output threads:	1 x G 1/8" female
Output adapters (hand-tightened and removable):	Standard delivery: <ul style="list-style-type: none"> G 1/8" / 60-G1/8" Nipple for 4 mm ID hose
Temperature:	0...50 °C / 32...122 °F
Humidity:	< 95% RH
Adjusting fineness:	0.001 mbar / 0.01 mmH ₂ O
Safety pressure:	< 4 bar / 1 600 iwc
Pressure media:	Air
Dimensions:	24 cm x 11 cm x 14 cm 9.45" x 4.33" x 5.51"
Weight:	1.2 kg / 2.6 lb
Standard delivery:	<ul style="list-style-type: none"> Output Connectors: <ul style="list-style-type: none"> G 1/8" / 60-G1/8" installed in the pump Nipple for 4 mm ID hose A small bag (10 pcs.) of o-rings in size and type: 10.1 mm x 1.6 mm NBR 70 User Guide
Optional accessories:	<ul style="list-style-type: none"> Carrying case Maintenance kit Extra output Connectors (same as in the standard delivery) Lubricant for the axle of the pressure adjust and fine adjustment handles

Beamex EXT

EXTERNAL PRESSURE MODULES



Increased usability with EXT modules

The Beamex EXT external pressure modules introduce new configuration possibilities and add flexibility, as it is possible to calibrate more pressure ranges with the same calibrator. This way, the Beamex calibration equipment meets your needs even better. Beamex offers a wide range of external pressure modules – from vacuum to 1000 bar / 14 500 psi. External pressure modules are compatible with Beamex MC6, MC5, MC4, MC2 MC5-IS, MC2-IS and MC5P calibrators.

78077348738843
11790865495495
780740254025402
529879959838458
800548757388434900

External pressure modules

MODULES ¹⁾	RANGE ²⁾	RESOLUTION	ACCURACY ³⁾ (±)	1 YEAR UNCERTAINTY ⁴⁾ (±)
EXT B EXT B-IS	80 to 120 kPa a 800 to 1200 mbar a 11.6 to 17.4 psi a	0.01 0.1 0.001	0.03 kPa 0.3 mbar 0.0044 Psi	0.05 kPa 0.5 mbar 0.0073 psi
EXT10mD EXT10mD-IS	±1 kPa diff ±10 mbar diff ±4 iwc diff	0.0001 0.001 0.001	0.05% Span	0.05% Span + 0.1% RDG
EXT100m EXT100m-IS	0 to 10 kPa 0 to 100 mbar 0 to 40 iwc	0.0001 0.001 0.001	0.015% FS + 0.0125% RDG	0.025% FS + 0.025% RDG
EXT400mC EXT400mC-IS	±40 kPa ±400 mbar ±160 iwc	0.001 0.01 0.001	0.01% FS + 0.0125% RDG	0.02% FS + 0.025% RDG
EXT1C EXT1C-IS	±100 kPa ±1 bar -14.5 to 15 psi	0.001 0.00001 0.0001	0.007% FS + 0.0125% RDG	0.015% FS + 0.025% RDG
EXT2C EXT2C-IS	-100 to 200 kPa -1 to 2 bar -14.5 to 30 psi	0.001 0.00001 0.0001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
EXT6C EXT6C-IS	-100 to 600 kPa -1 to 6 bar -14.5 to 90 psi	0.01 0.0001 0.001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
EXT20C EXT20C-IS	-100 to 2000 kPa -1 to 20 bar -14.5 to 300 psi	0.01 0.0001 0.001	0.005% FS + 0.01% RDG	0.01% FS + 0.025% RDG
EXT60 EXT60-IS	0 to 6000 kPa 0 to 60 bar 0 to 900 psi	0.1 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
EXT100 EXT100-IS	0 to 10 MPa 0 to 100 bar 0 to 1500 psi	0.0001 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
EXT160 EXT160-IS	0 to 16 MPa 0 to 160 bar 0 to 2400 psi	0.0001 0.001 0.01	0.005% FS + 0.0125% RDG	0.01% FS + 0.025% RDG
EXT250 EXT250-IS	0 to 25 MPa 0 to 250 bar 0 to 3700 psi	0.001 0.01 0.1	0.007% FS + 0.0125% RDG	0.015% FS + 0.025% RDG
EXT600 EXT600-IS	0 to 60 MPa 0 to 600 bar 0 to 9000 psi	0.001 0.01 0.1	0.007% FS + 0.01% RDG	0.015% FS + 0.025% RDG
EXT1000 EXT1000-IS	0 to 100 MPa 0 to 1000 bar 0 to 15000 psi	0.001 0.01 0.1	0.007% FS + 0.01% RDG	0.015% FS + 0.025% RDG

Temperature coefficient ±0.001% Rdg/°C outside 15...35 °C (59...95 °F)
INT10mD / EXT10mD < ±0.002% Span/°C outside 15...35 °C (59...95°F)

1) IS version available for all external pressure modules

2) Every internal/external pressure module's range may also be displayed in absolute pressure if the Barometric Module (B) is installed.

3) 'Accuracy' includes hysteresis, nonlinearity, repeatability and reference standard uncertainty (k=2).

4) '1 Year Uncertainty' includes hysteresis, nonlinearity, repeatability and typical long-term stability for mentioned period (k=2).

All external pressure modules (EXT) are also compatible with Beamex MC6, MC5, MC4, MC2 and MC5P calibrators. All intrinsically safe external pressure modules (EXT-IS) are compatible with Beamex MC5-IS and MC2-IS calibrators.

Supports the following pressure units as standard:

Pa, hPa, kPa, MPa, mbar, bar, lbf/ft², psi, gf/cm², kgf/cm², kgf/m², kp/cm², at, mmH₂O, cmH₂O, mH₂O, iwc, ftH₂O, mmHg, cmHg, mHg, inHg, mmHg(0 °C), inHg(0 °C), mmHg(4 °C), inHg(4 °C), ftHg(4 °C), inHg(60°F), mmHg(68°F), inHg(68°F), ftHg(68°F), torr, atm.

INT B / EXT B; M5 (10/32") female.

INT10mD and EXT10mD; Two M5 (10/32") female threads with a hose nipple included.

INT100m/EXT100m – INT20C/EXT20C; G1/8" (ISO228/1) female. A conical 1/8" BSP male with 60° internal cone adapter included for Beamex hose set.

INT60, INT100, INT160; G1/8" (ISO228/1) female. EXT60, EXT100, EXT160, EXT250, EXT600, EXT1000; G ¼" (ISO228/1) male.

Wetted parts AISI316 stainless steel, Hastelloy, Nitrile rubber.

Maximum overpressure;

B module; 1200 mbar abs. 10mD module; 200 mbar. EXT600; 900 bar. EXT1000; 1000 bar.

For all other modules, the maximum overpressure is twice the nominal range.

HART is a registered trademark of HART Communication Foundation.

WORKSTATIONS



PORTABLE CALIBRATORS



PROFESSIONAL SERVICES



CALIBRATION SOFTWARE



beamex

WORLD-CLASS CALIBRATION SOLUTIONS

www.beamex.com